

ASSEMBLING & INSTALLATION INSTRUCTIONS PRODUCT# 8560

For Wall Mount Fixture

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER .

MOUNTING THE FIXTURE

Installation (see fig.1)

1. Shut off the power at the circuit breaker and remove old fixture, including the single bar.
2. Thread the pipe screw part way into the center hole of the single bar and secure with hex nut.
3. Attach the single bar to the junction box using two box screws. The side of the single bar marked "GND" must face out.
4. Thread end of pipe nipple(C) into the bottom of lamp body's (A) hook, and lock it appropriate until snug.
5. Raise the plastic shim and glass(D) over the end pipe nipple of lamp body then tighten it with the plastic shim ,iron shim and hex nut (G).
6. Attach the cover(E) onto the glass then tighten it with the finial(F).
7. Follow wiring instructions carefully (see fig.2)
8. Place the lamp body(A) onto the pipe screw then tighten it with the ball nut (B).
9. Install the light bulbs in accordance with the fixture's specifications. **DO NOT EXCEED THE MAXIMUM WATTAGE RATING!**

Wiring (see fig.2)

1. Connect the electrical wires as follows. Connect the black wire from the fixture to the black house (hot) Wire. Connect the white wire from the fixture to the white (neutral) house wire. Make sure all wire nuts are secured. You may wrap the connections with electrical tape.If your outlet box has a ground wire (green or bare copper) connect fixture's ground wire to it. Otherwise attach the bare copper fixture wire to the green ground screw on the single bar.
2. Tuck the wire connections neatly into the wall junction box.

Fig.1




Fig.2

