


Project:

Purolinear 360 LED Wall Bar Spec Sheet

SKU: 23QPCSR22R120PHA Learn more at:
<https://sonnemanlight.com/purolinear-360-led-wall-bar>

Description: A system of linear tubes, set within the geometry of surface-mounted cylinder brackets, rotate individually to direct the LED illumination in 360 degrees along their axis. Arranged in a linear pattern or along a single path, the possibilities for compositions are endless and unlimited in scalability. Set on a wall, in line behind a bed, the rotatable luminaires provide the variability of direct or indirect illumination.



Type #:

Dimensions

Height: 24.75"
Width: 24.75"
Extends: 2.75"
Minimum Extension: 2.75"
Maximum Extension: 2.75"
Shape: Square
Size: 24"

Installation

Installation: Licensed electrician required

Shade

Shade 1 Material: Optical Acrylic

General Listings

Features: ADA Compliant, Damp Rated
Certification: C-ETL-US
Color/Finish: Polished Chrome (.01)
Dark Sky Friendly: N

Electrical Specs

Bulb(s) Included?: Yes
Bulb 1 Type: Integral LED
Bulb Quantity: 4
Input Voltage: 100-277VAC
Wattage: 7
Initial Lumens: 2760
Delivered Lumens: 1960
Color Temperature: 3000K
CRI: 90
Power Supply Type: Driver
Power Supply Quantity: 1
Power Supply Location: Remote
Dimming Type: TRIAC/ELV/0-10V
Bulb Max Wattage: 7

Available Finishes

Available Finishes: Polished Chrome (.01), Satin Black (.25), Satin Chrome (.23), Satin White (.03)