


## ASSEMBLY INSTRUCTIONS



TO assemble safety cables:

1. Join fixture safety cables with safety cable from ceiling.
2. Wrap both safety cable around the cable lock nut.
3. Secure by tightening both the hex nuts.
4. Push the cable lock nut into outlet box.

## Elliot Large Pendant

Item # SK 5355

**WE RECOMMEND INSTALLATION OF THIS LIGHTING FIXTURE BE DONE BY A LICENSED ELECTRICIAN.**

**WARNING\*\*\*SWITCH OFF THE MAIN ELECTRICAL SUPPLY FROM THE MAIN FUSE BOX/CIRCUIT BREAKER BEFORE INSTALLATION.**


**INSPECT ITEM CAREFULLY BEFORE ATTEMPTING TO INSTALL. IF THERE IS ANY DAMAGE OR OBVIOUS DEFECT. DO NOT INSTALL.**

**ITEM MAY NOT BE RETURNED ONCE IT HAS BEEN INSTALLED.**

**NOTE: CAREFULLY UNPACK EACH PIECE IN TOP LAYER OF PACKING PRIOR TO REMOVING. RETAIN ALL PACKING MATERIAL UNTIL INSPECTION AND INSTALLATION ARE FINAL.**

1. Carefully remove all parts from the box.
2. Remove the collar loop (A) from the chain (E) by unscrewing the quick link (B).
3. A 1/4 IPS pipe must be installed through the outlet box and secured to a structural member of the building. This item must hang independently of the junction box. Then install the threaded nipple (I) into the 1/4 IPS PIPE.
4. Install the canopy (C) to collar loop (A) and secure with collar ring (D). If needed, adjust canopy height by loosening hex nuts and screwing collar loop (A) up or down then re-secure.
5. With the fixture dimension as a guide, shorten the chain (E) as needed using a pair of chain pliers (not included).
6. Open the chain quick link (B), then attach the chain quick link (B) to the collar loop (A). Secure the chain quick link (B).
7. Open the chain quick link (B) from the opposite side then attach to the fixture loop (F). Secure the chain quick link (B).
8. Weave the fixture wires and safety cable through the chain (E).
9. When you reach the canopy (C) and the collar loop (A), measure the wires then cut, be certain to leave enough length to connect inside of the outlet box.
10. Strip the insulation on the fixture wires about 5/8".
11. Loosen the collar ring (D) and let the canopy (C) slip down the chain (E) carefully.
12. Twist the fixture wires and safety cable together and push through the center hole of the collar loop (a) and come out from the hickey.
13. Run safety cable through junction box and install to structural member of the building. Secure using cable lock nut as shown in figure.
14. Connect the fixture ground wire to the ground wire in the junction box using the wire nut (J). IT IS IMPERATIVE THAT THIS FIXTURE BE GROUNDED.

## ASSEMBLY INSTRUCTIONS



## Elliot Large Pendant

Item # SK 5355

**WE RECOMMEND INSTALLATION OF THIS LIGHTING FIXTURE BE DONE BY A LICENSED ELECTRICIAN.**

**WARNING\*\*\*SWITCH OFF THE MAIN ELECTRICAL SUPPLY FROM THE MAIN FUSE BOX/CIRCUIT BREAKER BEFORE INSTALLATION. INSPECT ITEM CAREFULLY BEFORE ATTEMPTING TO INSTALL. IF THERE IS ANY DAMAGE OR OBVIOUS DEFECT. DO NOT INSTALL. ITEM MAY NOT BE RETURNED ONCE IT HAS BEEN INSTALLED.**

**NOTE: CAREFULLY UNPACK EACH PIECE IN TOP LAYER OF PACKING PRIOR TO REMOVING. RETAIN ALL PACKING MATERIAL UNTIL INSPECTION AND INSTALLATION ARE FINAL.**

15. Connect the fixture ribbed wire ( no marking) to the neutral wire in the junction box using the wire nut (J).
16. Connect the fixture smooth wire (with marking) to the hot wire in the junction box using the wire nut (J).  
DO NOT REVERSE THE HOT AND NEUTRAL CONNECTIONS OTHERWISE SAFETY WILL BE COMPROMISED.
17. Carefully tuck the wire connections into the junction box.
18. Install the canopy (C) to the junction box and secure with collar ring (D).
19. Remove the socket ring (H), then attach the shade (G) to the socket (F) and secure with the socket ring (H).
20. Insert light bulb (not included) into socket.
21. Installation is complete, turn on power at fuse or circuit breaker.

\*\*\*Clean with a dry, soft cloth only. Use no harsh abrasives or chemical agents.