

MR16LED103-6PK

CRI 80 3000K 500Lumens LED MR16

The high performance LED MR16 architectural form and versatility to make it an excellent choice for new construction

Performance



- LED MR16 is designed to provide 25,000 hours of life
- UL, for use in Dry

Construction

- Aluminum for excellent heat dissipation

Installation

- Size: $\Phi 1.97''(50\text{mm}) \times H 1.97''(50\text{mm})$



Specifications

Category	Spot Light	Individual Box Weight per Unit (Lbs)	0.09
Shape	MR16	Inner Package Length (Inch)	6.53
Bulb Base Type	GU5.3	Inner Package Width (Inch)	4.48
Bulb Base Finish	NO	Inner Package Height (Inch)	2.68
Color Temperature	3000K	Inner Package Weight Per Unit (Lbs)	0.68
Beam Angle	40°	Inner Package Quantity	6
Finish	White	Carton Package Length (Inch)	
CRI	80	Carton Package Width (Inch)	
Average Life (Hours)	25000	Carton Package Height (Inch)	
Estimated Yearly Energy Cost (11 ¢ /Kwh)	0.78	Carton Package Weight Per Unit (Lbs)	
Life Based On 3Hrs/Day (Years)	22.83	Carton Quantity	
Product Length (Inch)	N/A	Lamp Type	GU5.3
Product Width (Inch)	1.97	Bulb Shape	MR16
Product Height (Inch)	1.97	Dry/Wet/Damp	Dry
Product Extension (Inch)	N/A	Energy Star	NO
Product Weight Per Unit (Lbs)	0.07	Power Factor	0.7
Dimmable	YES	Current	64MA
Watts	6.5W	Lumen/Watt	77
Watt Equivalent	50	Warranty (Year)	3
Lumens	500	DLC (Yes/No)	NO
Certification (UL/ETL/FCC)	ETL	Input Voltage	12V
Individual Box Length (Inch)	2.05	Housing Material	Aluminum+PC
Individual Box Width (Inch)	2.05	Lens	PC
Individual Box Height (Inch)	2.28	Led Type	Bridgelux 2835