



# WAFER | FLUSH/WALL MOUNT

58710 / 58711 / 58712 / 58713 / 58714 / 58715 / 58736 / 58737 / 58780 /

58784 / 58810 / 58812 / 58814

Job Name : \_\_\_\_\_  
 Job Type : \_\_\_\_\_  
 Quantity : \_\_\_\_\_  
 Comments : \_\_\_\_\_

- New models feature 120-277V
- Die Cast Aluminum
- Edge Lit LED technology
- Available in Black, Bronze, Satin Nickel and White finishes
- Choice of 4 Size Options between 5" and 15"
- Thin profile of .5"
- Wet Location Rated
- Dimmable with Triac and ELV Dimmers, ELV only at 120V
- Energy Star
- T24 Options



**58780WT**  
7" Empty Shell



**58784WTWT**  
Wafer LED 7" RD w/ 1.5 hours  
Emergency Back Up



## PRODUCT DESCRIPTION

Wafer was designed for the discriminate consumer who wants the low profile look of recessed without the high cost. Manufactured of die cast aluminum, Wafer brings ultimate heat dissipation to its edge lit technology. Edge lighting gives very even light distribution while dispersing heat over a larger area. The result of this is longer LED life and better light diffusion.

## MEASUREMENTS

### MODEL DIMENSION

58710	5.5"W x 0.5"H x 5.5"L	58784	7"W x 2"H x 7"L
58711	5.5"W x 0.5"H x 5.5"L	58714	9"W x 1.5"H x 9"L
58810	5.5"W x 0.5"H x 5.5"L	58715	9"W x 0.5"H x 9"L
58712	7"W x 0.5"H x 7"L	58814	9.5"W x 0.5"H x 9"L
58713	7"W x 0.5"H x 7"L	58736	15"W x 0.5"H x 15"L
58812	7"W x 0.5"H x 7"L	58737	15"W x 0.5"H x 15"L

WIRE LENGTH 6"L

## LAMPING

MODEL	BULB TYPE	CRI	COL TEMP.	LUMENS RATED	LUMENS DEL	DIMMABLE	INPUT
58710	10W AC Integrated LED	90+	3000K	930	750	ELV	120-277V
58711	10W AC Integrated LED	90+	3000K	930	750	0-10V	120-277V
58712	15W AC Integrated LED	90+	3000K	1350	1100	ELV	120-277V
58713	15W AC Integrated LED	90+	3000K	1500	1200	ELV	120-277V
58714	20W AC Integrated LED	90+	3000K	2100	1700	0-10V	120-277V
58715	20W AC Integrated LED	90+	3000K	2250	1800	0-10V	120-277V
58736	30W AC Integrated LED	90+	3000K	3000	2400	ELV	120-277V
58737	30W AC Integrated LED	90+	4000K	3000	2400	0-10V	120-277V
58784	17W AC Integrated LED	90+	3000K	1250	1000	ELV	120-277V
58810	10W AC Integrated LED	90+	4000K	930	750	ELV	120-277V
58812	15W AC Integrated LED	90+	4000K	1500	1250	ELV	120-277V
58814	20W AC Integrated LED	90+	4000K	2200	1800	ELV	120-277V

Always consult a qualified electrician before installing any lighting product


## FINISHES OPTIONS:

White (WT)

Bronze (BZ)

Satin Nickel (SN)

Black (BK)



## MATERIAL:

Aluminum Construction  
Polycarbonate Lens

## AVAILABLE SIZES:

5.5" | 7" | 9" | 9.5" | 15"


## RATINGS:

cETLus  
Wet Location  
Energy Star  
Title 24 JA8 compliant  
ADA  
Dimmable:  
Closets Rated: 410.8 & 410.16



## ADDITIONAL:

RATED LIFE: 50,000 Hours  
OPERATING TEMP: -20° C (-4°), 40° C (104° F)  
PHOTOMETRIC: Report Found Online



**WESTERN DISTRIBUTION CENTER (HEADQUARTER)**  
253 NORTH VINELAND AVE | CITY OF INDUSTRY, CA 91746

**EASTERN DISTRIBUTION CENTER**  
4200 SHIRLEY DR. | ATLANTA, GA 30336

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com