


MSL1004

CRI 80 5000K 1400Lumens LED Security Light



The high performance LED Security Light architectural form and versatility to make it an excellent choice for new construction or retrofit applications.

Performance




- This LED security light is designed to provide 50,000 hours of life
- UL compliant, for use in Wet locations

Construction

- Die -cast aluminum housing with durable paint finish
- Plastic optical lens is protected by gasket lined tempered PC cover

Installation

- LED Security Light wall mount
- Size: L10.04"(255mm)*H6.61"(168mm) *W6.89"(175mm)



Specifications

Category	Motion Security Light	Individual Box LENGTH (INCH)	11.46
Bulb Shape	Round	Individual Box Width (INCH)	7.68
Bulb Base Type	Integrated LED	Individual Box HEIGHT (INCH)	7.28
Bulb Base Finish	N/A	Individual Box Weight per Unit (LBS)	3.18
Color Temperature	5000K		
Beam Angle	270°		
Finish	Black		
CRI	80		
Average Life (Hours)	50000		
Estimated Yearly Energy Cost (11 ¢ /Kwh)	2.41	Lamp Type	LED
Life Based On 3Hrs/Day (Years)	45.66	Dry/Wet/Damp	Wet
Product Length (Inch)	10.04	Energy Star	YES
Product Width (Inch)	6.89	Power Factor	0.9
Product Height (Inch)	6.61	Current	200mA
Product Extension (Inch)	N/A	Lumen/Watt	70
Product Weight Per Unit (Lbs)	2.43	Warranty (Year)	5
Dimmable	NO	DLC (Yes/No)	No
Watts	20W	Input Voltage	120V-277V
Watt Equivalent	75W	Housing Material	Aluminum
Lumens	1400	Lens	Polycarbonate
Certification (UL/ETL/FCC)	UL	Led Type	LG 3030