

WAC LIGHTING

Lotos R 4"

Adjustable Downlight 5CCT

Model	Beam	Color Temp & CRI	Lumens	CBCP	Finish
R4ERA2R	W 50	9CS 2700K/3000K/3500K/4000K/5000K - 90	740 775	733 750	BK Black WT White

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Example: **R4ERA2R-W9CS-BK**

DESCRIPTION

The wafer-thin Lotos LED Recessed Kit with remote driver combines highquality light output and efficiency while eliminating the need for a large housing. This innovative design can be installed easily as a remodel or new construction with an optional frame-in kit sold separately. Lotos is available in a downlight version for general ambient lighting and an adjustable version with a gimbal that pivots 360 degrees on a hinge. Now available with 5-CCT options.

FEATURES


- 5-CCT Switchable between 2700K and 5000K
- Multiple LED array for uniform illumination
- Rotatable multi-axis gimbal ring
- Driver included
- 5 year warranty

SPECIFICATIONS

Construction:	Steel with frosted TIR lens
Power:	9W
Input:	120 -277 VAC, 50/60Hz
Dimming:	ELV: 100-5% , TRIAC: 100-5%
Light Source:	Integrated LED
Lens:	Translucent acrylic diffuser
Rated Life:	50000 Hours
Mounting:	Heavy gauge retention clips secures fixture to ceiling
Cut Out:	4"
Finish:	Electrostatically powder coated: Black, White
Ceiling Thickness:	1/2" - 1"
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	ETL, cETL, Wet Location Listed, Energy Star 2.0, Title 24 JA8 Compliant, IC, Airtight




FINISHES:



Black

White

LINE DRAWING:



Lotos R 4" Adjustable
R4ERA2R-W9CS-WT

WAC LIGHTING

Lotos R 4"
Adjustable Downlight 5CCT

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

ACCESSORIES

<i>Model</i>	<i>Description</i>	<i>Finish</i>
--------------	--------------------	---------------
