


TUBE ARCHITECTURAL DS-WD06

WAC LIGHTING

LED Wall Mounts



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cylindrical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

FEATURES

- High performance exterior rated LED wall mount light
- Fixture can install upside down to alter light distribution
- Solid aluminum construction
- 5 year warranty

SPECIFICATIONS

Input:	Universal voltage 120V - 277VAC, 50/60Hz
Dimming:	Electronic low voltage (ELV) : 100% - 5% 0-10V: 100% - 1%
Light Source:	High output 3 Step Mac Adam Ellipse COB Rated life of 60,000 hours at L70
Finish:	Electrostatically powder coated, white, black, bronze and graphite
Standards:	IP65 rated, ETL & cETL wet location listed Title 24 JA8-2016 Compliant
Operating Temp:	-13°F to 122°F (-25°C to 50°C)

ORDERING NUMBER

Diameter	Watt	Beam	Beam Angle	Color Temp	CRI	Reference Output ¹		Efficacy (lm/w)	Light Distribution	Finish	
						Lumen	CBCP				
DS-WD06	6" 35W x 2	S Straight up and down	16°	927S	2700K	90	2820 x 2	18842 x 2	81 x 2		BK Black WT White BZ Bronze GH Graphite
				27S	2700K	85	3385 x 2	22608 x 2	97 x 2		
				930S	3000K	90	2925 x 2	19543 x 2	84 x 2		
				30S	3000K	85	3535 x 2	23632 x 2	101 x 2		
				35S	3500K	85	3630 x 2	24255 x 2	104 x 2		
				40S	4000K	85	3665 x 2	24490 x 2	105 x 2		
		N Straight up and down	28°	927S	2700K	90	2800 x 2	7992 x 2	80 x 2		
				27S	2700K	85	3360 x 2	9589 x 2	96 x 2		
				930S	3000K	90	2900 x 2	8290 x 2	83 x 2		
				30S	3000K	85	3510 x 2	10024 x 2	100 x 2		
				35S	3500K	85	3600 x 2	10288 x 2	103 x 2		
				40S	4000K	85	3635 x 2	10388 x 2	104 x 2		
		F Straight up and down	38°	927S	2700K	90	2825 x 2	5451 x 2	81 x 2		
				27S	2700K	85	3390 x 2	6540 x 2	97 x 2		
				930S	3000K	90	2930 x 2	5654 x 2	84 x 2		
30S	3000K			85	3545 x 2	6836 x 2	101 x 2				
35S	3500K			85	3640 x 2	7017 x 2	104 x 2				
40S	4000K			85	3675 x 2	7085 x 2	105 x 2				
DS-WD0644	6" 22W x 2	F Away from the wall	N/A	927A	2700K	90	2860 x 2	N/A	82 x 2		
				27A	2700K	85	3435 x 2	N/A	98 x 2		
				930A	3000K	90	2970 x 2	N/A	85 x 2		
				30A	3000K	85	3590 x 2	N/A	103 x 2		
				35A	3500K	85	3685 x 2	N/A	105 x 2		
				40A	4000K	85	3720 x 2	N/A	106 x 2		
		F Towards the wall	N/A	927B	2700K	90	2860 x 2	N/A	82 x 2		
				27B	2700K	85	3435 x 2	N/A	98 x 2		
				930B	3000K	90	2970 x 2	N/A	85 x 2		
				30B	3000K	85	3590 x 2	N/A	103 x 2		
				35B	3500K	85	3685 x 2	N/A	105 x 2		
				40B	4000K	85	3720 x 2	N/A	106 x 2		
F One side each	N/A	927C	2700K	90	2860 x 2	N/A	82 x 2	One side away from wall, one side towards the wall			
		27C	2700K	85	3435 x 2	N/A	98 x 2				
		930C	3000K	90	2970 x 2	N/A	85 x 2				
		30C	3000K	85	3590 x 2	N/A	103 x 2				
		35C	3500K	85	3685 x 2	N/A	105 x 2				
		40C	4000K	85	3720 x 2	N/A	106 x 2				

DS-WD06- _____ - _____ Example: **DS-WD06-F930A-WT** ¹Reference output shows 35W output. Multiply by 0.7 to determine output for 22W combinations.

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760