

COUNTERMAX 120V SLIM STICK I LED UNDERCABINET

88950/ 88951/ 88952/ 88953/ 88954/ 88955


- Driverless White Tunable between 2700-5000K*
- Full range dimming*
- Direct Wire box not included
- Available in White (WT) and Bronze (BZ)
- Linkable end to end or with MX Interlink Cord
- Use of Direct Wire Box is required to unlock all the features of the 120V Slim Stick
- CRI 90+
- ETL/ cETL IP65

Job Name : _____
 Job Type : _____
 Quantity : _____
 Comments : _____



PRODUCT DESCRIPTION

An innovative, slim channel LED light bar. The 120V input Slim Stick connects to a slim direct wire installation junction box where brightness and white color tunable LED light can be adjusted with the touch of a button. The control is the first in the industry to provide color temperature control variable between 2700-5000k on a driverless 120V LED strip. Included with the product, mounting clips allow the user install the channels flat or at an angle up to 90 degrees, so the product can be used in more applications such as cove, task, and closet lighting.



MEASUREMENTS

MODEL	DIMENSION	CRI	HCO
88950	6"L x 1.38" W x 86"H	90+	0.75
88951	12"L x 1.38" W x 86"H	90+	0.75
88952	18"L x 1.38" W x 86"H	90+	0.75
88953	24"L x 1.38" W x 86"H	90+	0.75
88954	30"L x 1.38" W x 86"H	90+	0.75
88955	36"L x 1.38" W x 86"H	90+	0.75

LAMPING

MODEL	BULB TYPE	COLOR TEMPERATURE	LUMENS RATED	LUMENS DEL	INPUT	DIMMABLE
88950	3W LED (Integrated)	5000K	300	150	120V	Triac CL
88951	6W LED (Integrated)	5000K	600	320	120V	Triac CL
88952	9W LED (Integrated)	5000K	900	480	120V	Triac CL
88953	12W LED (Integrated)	5000K	1300	800	120V	Triac CL
88954	15W LED (Integrated)	5000K	1600	1000	120V	Triac CL
88955	18W LED (Integrated)	5000K	1900	1250	120V	Triac CL

INCLUDES

- Mounting Clips included
- Always consult a qualified electrician before installing any lighting product*

OPTIONAL




Connector Cord
 9" 88963 BK, WT
 18" 88964 BK, WT
 24" 88965 BK, WT



Direct Wire Box
 88960 BK, WT
 6"L x 1.5"W x 1"H

FINISHES OPTION



MATERIAL

Aluminum + LED + PC

RATINGS

cETLus
 Dry Location
 Energy Star
 JA8 Listed



ADDITIONAL

RATED LIFE 40000 Hours
 OPERATING TEMPERATURE:
 -20°C (-4°F), 40°C (104°F)



WESTERN DISTRIBUTION CENTER (HEADQUARTER)
 253 NORTH VINELAND AVE | CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER
 4200 SHIRLEY DR. | ATLANTA, GA 30336

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com