

## Paloma LED522 22W Monopoint Luminaire

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

System Type	Model	Beam	Color Temp & CRI		Lumens	CBCP	Finish		
MO	LED522	F 36°	827	2700K - 85	1630	4048	BK	Black	
			830	3000K - 85	1695	4218	WT	White	
			835	3500K - 85	1745	4345			
			840	4000K - 85	1765	4385			
			927	2700K - 90	1355	3375			
			930	3000K - 90	1695	3500			
			N 24°	827	2700K - 85	1650	5928		
				830	3000K - 85	1625	6177		
				835	3500K - 85	1675	6362		
		840		4000K - 85	1690	6422			
		927		2700K - 90	1301	4940			
		930		3000K - 90	1350	5125			
		S 19°	827	2700K - 85	1590	7622			
			830	3000K - 85	1655	7940			
			835	3500K - 85	1705	8180			
			840	4000K - 85	1720	8257			
			927	2700K - 90	1325	6352			
			930	3000K - 90	1375	6590			

Example: **MO-LED522F-827-BK**

### DESCRIPTION

Paloma is a museum-quality LED luminaire with high performance reflector optics. Available in 12W or 22W options in multiple color temperature, beam distribution, and finish options. Canopy is included with fixture. Monopoint can be ordered with an extension rod (6", 12", 18", 24", 36") to drop the head.

### FEATURES


- Accommodates 1 filter lens or 1 accessory
- 365° horizontal rotation and 180° vertical aiming
- Ceiling and wall mountable
- Driver concealed within the fixture
- 5 year warranty

### SPECIFICATIONS

<b>Construction:</b>	Die-cast aluminum with cap ring. Clear glass lens included
<b>Power:</b>	22W
<b>Input:</b>	120-277 VAC, 50/60Hz
<b>Dimming:</b>	ELV: 100-5%
<b>Light Source:</b>	Integrated LED 3 Step Mac Adam Ellipse
<b>Rated Life:</b>	50000 Hours
<b>Finish:</b>	Electrostatically Powder Coated White, Black
<b>Operating Temp:</b>	-4°F to 104°F (-20°C to 40°C)
<b>Standards:</b>	UL, cUL, Damp Location Listed




### FINISHES



Black White

### LINE DRAWING



Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

## Paloma LED522 22W Monopoint Luminaire

### ACCESSORIES

	<i>Model</i>	<i>Description</i>	<i>Finish</i>
	<b>LENS-20-AMB</b> <b>LENS-20-BLU</b>	<i>Colored Lens</i> <i>Colored Lens</i>	<i>Amber</i> <i>Blue</i>
	<b>LENS-20-CL</b>	<i>Clear/Frosted Lens</i>	<i>Clear</i>
	<b>LENS-20-SPR</b>	<i>Spread Lens</i>	<i>Spread Lens</i>
	<b>LENS-20-BEL</b>	<i>Beam Elongating Lens</i>	<i>Beam Elongating</i>