



Assembly Instructions for 3062

We recommend installation of this fixture be done by a licensed electrician. Turn off powder at the main fuse or circuit breaker box. **DO NOT EXCEED RECOMMENDED WATTAGE!**

**** Actual parts may vary slightly depending upon the model**

1. Remove the parts carefully from the box before discarding the carton.
2. Attach round cross bar with strip to the outlet box with ground screw facing out.
3. Use Philips screwdriver to unscrew 4 Frame screws and remove lamp cluster from the frame.
4. Glass installation: Remove nut and clip from top/bottom frame. Align & place the clear glass panel between vertical strip of the frame, place clip on top & bottom of frame & tighten the nut. After installing all 4 glass panels, insert lamp cluster into the frame & fasten lamp cluster to the frame using 4 frame screws.
5. Install bulbs (not included)
6. Determine hanging length and which stem(s) will be used together or by itself. Options are 1pc 3" stem, 1 pc 6" and 2pcs of 12" stems.
7. Slip lead wire through the stems and screw the stem(s) into fixture's pipe on one and canopy on the other end.
8. Note canopy comes with 60 degrees swivel to accommodate sloped ceiling.
9. Fasten ground wire to green screw, Fasten lead wire (or white wire) with ridges to the white wire. Use wire nut to fasten it.
10. Fasten smooth (or black wire) lead wire to the black wire in the box & use nut to fasten it.
11. Place the canopy over the outlet box with holes on the canopy aligning with the strip.
12. Secure the fixture using side screws.
13. Restore circuit breaker

