

# WAC LIGHTING

## VENTRIX

### Stealth Downlights

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

Model & size	Power	Watt	Beam	Color Temp & CRI	Delivered Lumens	CBCP	Finish
S2SD	1	8.5W	F 50°	927 2700K - 90	540	790	BK Black
	1	8.5W	F 50°	930 3000K - 90	570	830	CH Chrome
	1	8.5W	F 50°	935 3500K - 90	600	870	GL Gold
	1	8.5W	F 50°	940 4000K - 90	610	890	HZ Haze
	1	8.5W	N 32°	927 2700K - 90	580	1760	WT White
	1	8.5W	N 32°	930 3000K - 90	610	1850	
	1	8.5W	N 32°	935 3500K - 90	640	1940	
	1	8.5W	N 32°	940 4000K - 90	650	1980	
	1	8.5W	S 19°	927 2700K - 90	420	2420	
	1	8.5W	S 19°	930 3000K - 90	440	2550	
	1	8.5W	S 19°	935 3500K - 90	460	2670	
	1	8.5W	S 19°	940 4000K - 90	470	2720	

Example: **S2SD-1-F927BK**

#### DESCRIPTION

Installed anywhere along the channel or side by side in pairs, Stealth Downlights provide clear, task illumination with virtually no glare. Finish options complement other elements in your VENTRIX array, and field changeable optics and trims add another level of design customization.

#### FEATURES


- Low glare trim with 30° shielding angle
- Interchangeable trim available in 5 finishes
- May be installed side by side or at end of VENTRIX channel
- Stealth Downlight may be installed in corners or at the end of channel.
- To enable access to VENTRIX element releasing tabs, maintain at least 3" of free channel space
- Driver concealed within the fixture
- 5 year warranty

#### SPECIFICATIONS


<b>Construction:</b>	Die-cast aluminum with injection molded low glare trim
<b>Power:</b>	8.5W
<b>Input:</b>	48 VDC
<b>Dimming:</b>	ELV: 100-0.1% , 0-10V: 100-0.1%, TRIAC: 100-0.1%
<b>Light Source:</b>	Integrated LED
	3 Step Mac Adam Ellipse
<b>Rated Life:</b>	50000 Hours
<b>Mounting:</b>	Installs magnetically and mechanically into VENTRIX system, Can be mounted on ceiling or wall vertically or horizontally
<b>Finish:</b>	Injection Molded Polycarbonate: Chrome, Gold, Haze, Black, White
<b>Operating Temp:</b>	-4°F to 104°F (-20°C to 40°C)
<b>Standards:</b>	UL, cUL, Dry Location Listed, Title 24 JA8 Compliant



#### FINISHES:



#### LINE DRAWING:



#### REPLACEMENT PARTS

- REF-S2SD02-BK - Stealth Downlight Trim
- REF-S2SD02-CH - Stealth Downlight Trim
- REF-S2SD02-GL - Stealth Downlight Trim
- REF-S2SD02-HZ - Stealth Downlight Trim
- REF-S2SD02-WT - Stealth Downlight Trim