

Item # F656L-PN Product Family Name: Contractor Uni-Pack LED Category: INTERIOR FAN Certification 4000048 Patents:

Notes:

UPC Code: 706411055119 Finish: Polished Nickel Category Type: Ceiling Fan



Image File Name: F656L-PN.jpg



Blade Finish:			Reversible Blades: No
Blade Material: PLYWOOD W/PAPER OVERLAY			Slope: No
Blade Sweep:	No. of Blades:	Blade Pitch:	Hanging Weight:
52"	5	12 DEGREES	19.14
Downrod 1:	Downrod 1 OutsideDownroad 2:		Downrod 2 Outside
6	Dia:		Dia:
	0.75		
Ceiling to Lowest	Ceiling to Blade	Lead Wire:	Motor Size:
Point: (Dim A)	(Dim B)	80"	172X14MM
14.5	10.0		

LAMPING

No. of Bulbs: 1 Max Bulb Wattage: 26	Light Type: Z26,LED Socket: Y22,LED			
Light Kit: Yes	Dimmable: No	Ballast:	Rated Life Hours: 30000	Uplight: No
Bulb/LED Included: Yes	Color Temp.: 3000	CRI: 82	Initial Lumens: 2329.2	Delivered Lumens: 1647.0

	Low	Low/Med.	Medium	Med/High	High	
RPM:	58		126		197	
Amps:	0.22		0.41		0.62	
Watts:	8.8		31.1		74.6	
CFM:	1583.0		3716.0		5994.0	
CFM/Watts:	179.89		119.49		80.35	

GLASS

Description: Frosted White		Material: GLASS
Part No.:		Quantity:
Width: 12.25	Height:	Length: 12.25



FAN CONTROLS

Pull Chain Control: Yes	Works with Remote Control: Yes	Works with Wall Control: Yes
	Included Remote Control:	Included Wall Control:
	Compatible Remote Control(s): RCS223	Compatible Wall Control(s): WCS223

LED

LED



Carton Width: 14.25 Carton Weight: 22.37	Carton Height: 8.63 Carton Cubic Feet: 1.886	Carton Length: 26.5 Small Package Shippable: Yes
Master Pack Width:	Master Pack Height:	Master Pack Length:
Master Pack Weight:	Master Cubic Feet:	Multi-Pack: Master Pack: 1 1



ETL Intertek

For additional information, please contact Customer Care: 1-800-221-7977 | Product depicted on this spec sheet is protected by United States Federal and/or State laws including US Patent, Trademark and/or Copyright and unfair competition laws. Unauthorized reproduction or use carries severe legal penalties.