


Project:

Thin-Line Indirect LED Wall Bar Spec Sheet

SKU: 2814.25-8 Learn more at:
<https://sonnemanlight.com/thin-line-indirect-led-wall-bar>

Description:

A system of minimally scaled LED indirect light wall bars, uplight/downlight wall bars, and pendants. Thin-Line is offered in a variety of lengths, finishes, and lighting configurations. Indirect configurations reflect light back onto the wall or mounting surface to radiate indirect illumination.



Type #:



Dimensions

| | |
|-------------------------------|-------|
| Height: | 0.75" |
| Width: | 96" |
| Extends: | 3.5" |
| Minimum Extension: | 3.5" |
| Maximum Extension: | 3.5" |
| Size: | 8' |
| Canopy/Backplate/Base Width: | 1 |
| Canopy/Backplate/Base Height: | 0.75 |

Electrical Specs

| | |
|------------------------|--------------|
| Bulb(s) Included?: | Yes |
| Bulb 1 Type: | Integral LED |
| Bulb Quantity: | 1 |
| Input Voltage: | 120VAC |
| Wattage: | 47 |
| Initial Lumens: | 3120 |
| Delivered Lumens: | 1800 |
| Color Temperature: | 3000K |
| CRI: | 90 |
| Power Supply Type: | Driver |
| Power Supply Quantity: | 1 |
| Power Supply Location: | Remote |
| Dimming Type: | TRIAC/ELV |
| Bulb Max Wattage: | 47 |

Installation

| | |
|---------------------------|-------------------------------|
| Installation: | Licensed electrician required |
| Installation Orientation: | Any Orientation |

Shipping

| | |
|------------------------|---------------|
| Carton 1 L x W x H: | 99" X 7" X 4" |
| Carton 1 Gross Weight: | 8 LBS |

Shade

| | |
|-------------------|----------------------------|
| Shade 1 Material: | Aluminum w/Optical Acrylic |
|-------------------|----------------------------|

Available Finishes

Available Finishes: Bright Satin Aluminum (.16), Satin Black (.25), Satin White (.03)

General Listings

| | |
|--------------------|---------------------|
| Features: | Damp Rated, On Sale |
| Certification: | C-ETL-US |
| Color/Finish: | Satin Black (.25) |
| Dark Sky Friendly: | N |