



SKIP

12V MINI PENDANTS

location:
DRY

SPECIFICATIONS:

DESCRIPTION

Low voltage mini pendant with concrete shade.

LAMPING

Standard: 35W Shielded flood 12V halogen MR16 lamp, lamp included.

LED: 7W Replaceable 12V LED MR16, dimmable, 82+ CRI, 3000°K CCT, 500 lumens, 25,000 hours. Lamp included.

DIFFUSER

Shade shall be made of concrete in various finishes. 4" L x 4" W x 6" H

CORD

Standard cord is 10' field-adjustable coaxial type with teflon jacket and decorative sleeve at the socketholder. Jacket tint coordinates with metal finish.

STANDARD PENDANT

Mini pendant comes complete with flat-style canopy.

METAL FINISH


Hardware and canopies are finished in Bronze or Satin Nickel.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



WHITE (SKIPWH) & TAN (SKIPTN) WITH BRONZE FINISH



SKIPNA
NATURAL



For ordering information, see next page

All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 3/16



SKIP

12V MINI PENDANTS


ORDERING:

CONNECTION	SHADE OPTIONS	LAMP OPTIONS	METAL FINISH
Pendant Fixtures	SKIPNA Natural	(blank) 35W MR16 Hal	BR Bronze
1XT Flat Canopy	SKIPTN Tan SKIPWH White	LED 7W LED	SN Satin Nickel

Ex. 1XT-SKIPWH-SN
Skip Pendant, White,
Satin Nickel Finish

FIXED PENDANT OPTION:

1XT 1 Light Pendant, Flat Canopy



- Suitable for use on sloped ceilings
- 1x electronic 60W dimmable 120V transformer, fits partially in junction box
- Installs to standard 4" octagonal junction box
- Bronze or Satin Nickel metal finishes

12V LED MR16 TYPE LAMPS:

Design includes thermal fins and construction for heat management and increased LED life.

7W Replacable LED:

- 7W LED lamp
- 500 lumens
- 12V input only
- Rated life: 25,000 hours
- CRI: 82+
- CCT: 3000°K
- Dimmable
- **Item #: B5552**

Project Information: