


MODEL NAME **SPN6SQ-CC-3T**
MYSTIQUE
6-Inch Square Recessed Panel Light With Interchangeable Trims

If you are looking for a sleek, attractive LED option for your ceilings, then our color changing panel light with interchangeable trims is the perfect choice.



PROJECT:	TYPE:
DATE:	QTY:
NOTES:	




QUICK SPECS

SIZE	WATTS	DELIVERED LUMENS*	COLOR °T 3CCT	CRI	VOLTAGE	BEAM ANGLE	FINISH
6"	14W	1060lm	3000K 4000K 5000K	90	120V	110°	<input type="radio"/> White <input type="radio"/> Satin Nickel <input type="radio"/> Black

*Lumen output measured at 3000K

LIGHT DISTRIBUTION



CONSTRUCTION

Lens Frosted	Type of optics Flat lens	Type of LED Edge-lit SMD
Lens material Acrylic	Housing material Cast aluminum	Cut hole size 6-1/2"

RATINGS

Placement Indoor/Outdoor	Lifespan 50,000 hrs.	FT rating FT6
Location Wet	Certifications ETL, FCC, ICES, ES IC, ASTM E283-04, T24	Operating temperature -20° to 40° C

WHAT'S IN THE BOX

- LED recessed fixture
- Junction box
- Push-in wire connectors
- Interchangeable trims
- Mounting hardware
- Instruction sheet

ACCESSORIES

- RFP-UNI**
Universal Drilling Plate
- RFP-46**
Drilling Plate

ADAPTERS

- REC-EXT108**
108" extension cord for recessed fixtures
- REC-EXT230**
230" extension cord for recessed fixtures



ELECTRICAL DETAILS	Input voltage 100-135V	Output current 320mA	Power factor 99%	Driver type Constant current
	Output voltage 36V	LED model # 2835	THD harmonic distortion <30%	Binning type 3 SDCM

FEATURES	Every fixture includes a junction box with an integrated driver	Superior LED performance and lifespan	Minimal heat emission	Very low profile	3 interchangeable trim colors
	Can be daisy chained	Smooth 360° wide spread	Frosted lens	Switch-selectable CCT: 3000 K/ 4000 K/ 5000 K	
			Edge lit technology		

WARRANTY DALs offers a 5-year warranty from the date of purchase which covers repairs or replacement of defective parts of the housing, optics, and electronics. To contact DALs customer service call 1-877-430-1818 or send an e-mail to info@dals.com.

RECOMMENDED DIMMER LIST*

BRAND	MODEL #	DIMMER SPECS	GRADE	DIMMING RANGE (%)	MAX LOAD
Dals	SM-DIMSW Smart Dimmer	Triac, 250W LED/CFL	Compatible	Min: 8 / Max: 99	17
Lutron	DVCL-153PR-WH-C	Triac, 150 W Dimmable CFL/LED	Compatible	Min: 12 / Max: 100	10
Lutron	CTCL-153PDH-WH-C	Triac, 150 W Dimmable CFL/LED	Compatible	Min: 8 / Max: 100	10
Lutron	STCL-153PH-WH-C	Triac, 150 W Dimmable CFL/LED	Compatible	Min: 7 / Max: 100	10
Lutron	DVWCL-153PH-WHC	Triac, 150 W Dimmable CFL/LED	Compatible	Min: 8 / Max: 100	10
Lutron	MACL-153MRHW-WHC	Triac, 150 W Dimmable CFL/LED	Compatible	Min: 2 / Max: 100	10
Lutron	DVELV-300P-WH	300W electronic low voltage dimmer	Compatible	Min: 9 / Max: 100	21
Lutron	MA-PRO-WH	ELV, 250W LED/CFL	Compatible	Min: 2 / Max: 100	17
Lutron	Caseta PD-6WCL-WH-R-C	Triac, 300W Dimmable CFL/LED	Compatible	Min: 3 / Max: 100	21
Lutron	Caseta PD-5NE-WH-C	ELV, LED—up to 250 W	Compatible	Min: 4 / Max: 100	17
Lutron	Caseta PD-10NXD-WH	Triac, LED—up to 250 W	Compatible	Min: 1 / Max: 100	17
Leviton	6672-1LW	Triac, 150W Dimmable CFL/LED	Compatible	Min: 25 / Max: 100	10
Leviton	DSM10	Triac, 450W Dimmable CFL/LED	Compatible	Min: 21 / Max: 100	32
Leviton	6674	Triac, 150 W Dimmable CFL/LED	Compatible	Min: 11 / Max: 100	10
Leviton	IPL06-10Z	Triac, 150 W Dimmable CFL/LED	Compatible	Min: 18 / Max: 100	10
Leviton	DSL06-752	Triac, 150 W Dimmable CFL/LED	Compatible	Min: 12 / Max: 100	21
Leviton	D26HD-742-1RW	Triac, 300W LED/CFL	Compatible	Min: 8 / Max: 99	17
Legrand	RHCL453PNICCV4	Triac, 450W Dimmable CFL/LED	Compatible	Min: 11 / Max: 100	32
Legrand	ADTP703TUM4	Triac, 450W Dimmable CFL/LED	Compatible	Min: 13 / Max: 100	32
Legrand	ADPD453LM2	Triac, 450W Dimmable CFL/LED	Compatible	Min: 39 / Max: 100	32
Legrand	RHL373PW	Triac, 250W LED	Compatible	Min: 8 / Max: 100	17
Control 4	C4-APD120-WH	ELV, 120W LED	Compatible	Min: 0 / Max: 99	8
Control 4	C4-FPD120-WH	Triac, 200W LED	Compatible	Min: 0 / Max: 99	14

* Minimal buzzing noise may occur with some dimmers