
ASSEMBLY AND INSTALLATION INSTRUCTIONS

W0162 / W0163

WARNING: TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER WHILE INSTALLING OR SERVICING THIS FIXTURE.

NOTES: 1. Before installing, consult local electrical codes for wiring and grounding requirements. 2. Read and save these instructions.



Turn off the power at fuse or circuit box.


- Thread two headless screws (D) through the mounting plate (A), then secure them with four lock nuts (G) (two on each side of the mounting plate). Adjust the length of the headless screws (D) if necessary.
 Note: Make sure that the headless screws are lined up horizontally, to ensure that the fixture will be level.
- 2. Attach the mounting plate (A) to the outlet box by using two mounting screws (B).
- 3. Pull out the source wires from the outlet box. Make wire connections using wire connectors (E) as follows:
 - ---Connect the hot wire (black insulation) from the fixture to the black wire from the power source.
 - ---Connect the neutral wire (white insulation) from the fixture to the white wire from the power source.
 - ---Attach the fixture ground wire (bare wire) to the mounting plate (A) with the green ground screw (C). Then connect it to the house ground wire with the wire connector (E).
 - Carefully put the wires back into the outlet box.




- 4. Attach the backplate to the mounting plate (A) by inserting two headless screw (D), then secure it with two bolt nuts (F).
- 5. Attach the glass shades to the glass brackets, secure them with socket rings.
- 6. Install bulbs (not included). See relamping label at socket area or packaging for maximum allowed wattage.

Turn on the power at fuse or circuit box.

The following parts are available for reorder if damaged or missing.





1 Year Warranty

Vaxcel warrants all of our products against defects in workmanship and finishes for one year following the date of shipment.

Exclusions: This warranty does not include the failure of products from extreme acts of nature; environmental conditions not suited for the products intended use; operation in temperatures outside of the range specified in the instruction manual; usage with improper power supply, power surges or dips. For coastal locations, some corrosion is considered normal for the environment.

Vaxcel reserves the right to repair, replace or issue a credit for any properly installed product, provided it is returned per RMA instruction. This warranty is limited to the cost of the product only and does not extend to transportation, installation or replacement costs.

How can warranty service be obtained? info@vaxcel.com 1-800-482-9235

