## LED Flush Mount

## FM1512 INSTALLATION SHEET

## START FROM HERE

- Make sure POWER is COMPLETELY OFF at the fuse box
- Have your fixture installed by a qualified licensed electrician
- Prepare everything in a clear area
- Wear gloves at all time during this installation
- Read instructions carefully before you start assembly
- Keep this installation sheet for future reference

Technical Support: 1-855-855-8926

- **1.** Remove fixture from its original package
- 2. Attach crossbar (1c) to electrical junction box (1a) using junction box screws (1e) provided in hardware package
- Make proper electrical connections (black to hot "L", white to neutral "N", ground to "GND") with wire nuts (1b) provided in hardware package
- **4.** Install Pan-Head Crossbar Mounting Screws **(1d)** halfway into threaded holes on crossbar **(1c)**. Align keyholes on backplate **(2a)** and module to Pan-Head Crossbar Mounting Screws **(1d)** heads, insert and turn, and then secure with screw driver
- Gently pull back clips (2b) to secure glass (3a) onto backplate (2a), followed by the ring (3b) until it clicks into place (Note: do not apply too much pressure, as excessive pressure will cause the glass to crack or break)

## Please Note:

- This Kuzco LED fixture comes with pre-wired LED module(s).
- Unless instructed to do so, please do not touch any part of the LED module(s) as any unnecessary contact with the module could cause permanent damage.
- For dimming, an ELV (Electronic Low Voltage) type of dimmer is required.
- 120V input



