

NLOPAC-R6T24

6" AC T24 Opal - LED Surface Mount

Source: 16W LED
1050lm

Type

Project

Catalog No.

Notes

PRODUCT DESCRIPTION

The AC Opal LED Series LED fixture is designed to surface mount over a standard junction box. The low profile dimmable luminaire produces even illumination and is cULus listed for wet locations.

FEATURES

- AC LED (No Driver)
- Dimmable
- 2700K or 4000K @ 90+ CRI (3000K available with [NLOPAC-R6509T24](#))
- Mount on standard 4" junction box
- ENERGY STAR certified

SPECIFICATION

Construction: One piece aluminum die formed housing and trim. Aluminum body dissipates heat and extends life.

Mounting: AC Opal (no driver) is flat on the back and suitable for installation on most 4" octagon boxes or 4/0 plaster ring. Luminaires can be installed in covered ceiling and wall mount. Luminaires can also be mounted on 5" or 6" recessed housings using optional torsion spring kit (NLOPAC-56RECKIT-2).

Optics: Nora specified and designed precision molded lens for optimal lumen output and even distribution.

Ratings: IC rated when used with a 4" electrical junction box rated for direct contact with insulation. Fire rated when used with a fire rated junction box.

ELECTRICAL

Input Voltage: 120V

Operating temperature: 0-45°C

Lumens / Wattage: 1050lm / 16W

Color Temperature: 2700K or 4000K (3000K available with [NLOPAC-R6509T24](#))

Color Rendering Index: 90+

Dimming: 5% with Triac or 10% with ELV

[Click Here](#) or check complete dimmer list at www.NoraLighting.com in the "Compatibility" page under "Resources" tab

ACCESSORIES

NLOPAC-56RECKIT-2: Opal can be mounted on 5" or 6" recessed housings using optional torsion spring kit.


NLOPAC-4BKT-2: Universal bracket for mounting 6" Opal to 3" or 4" junction boxes.

LISTING

- cULus Listed for wet locations (covered ceiling only)
- ENERGY STAR certified
- [5-Year Limited Warranty](#)
- RoHS Compliant
- Certified to the high efficacy requirements of California Title 24 JA8-2019
- Suitable for use in closets when installed in accordance to NEC Section 410.16 (A)(1) and 410.16 (C)(1).



PRODUCT IMAGES AND DIMENSIONS



NLOPAC-56RECKIT-2
Retrofit Kit for 5" or 6" Recessed Housings



NLOPAC-4BKT-2
Universal Bracket for 3" or 4" Junction Boxes

6" AC T24 Opal - LED Surface Mount

Color Temperature / Finish

NLOPAC-R6T2427BZ = 2700K / Bronze

NLOPAC-R6T2427NM = 2700K / Natural Metal (Discontinued, direct replacement: [NLOPAC-R6509T2427NM](#))

NLOPAC-R6T2427W = 2700K / White (Discontinued, direct replacement: [NLOPAC-R6509T2427W](#))

NLOPAC-R6T2430BZ = 3000K / Bronze (Discontinued, direct replacement: [NLOPAC-R6509T2430BZ](#))

NLOPAC-R6T2430NM = 3000K / Natural Metal (Discontinued, direct replacement: [NLOPAC-R6509T2430NM](#))

NLOPAC-R6T2430W = 3000K / White (Discontinued, direct replacement: [NLOPAC-R6509T2430W](#))

NLOPAC-R6T2440BZ = 4000K / Bronze

NLOPAC-R6T2440NM = 4000K / Natural Metal (Discontinued, direct replacement: [NLOPAC-R6509T2440NM](#))

NLOPAC-R6T2440W = 4000K / White (Discontinued, direct replacement: [NLOPAC-R6509T2440W](#))

Optional Accessories

Description

NLOPAC-56RECKIT-2 = Retrofit Kit for 5" or 6" Recessed Housings

NLOPAC-4BKT-2 = Universal Bracket for 3" or 4" Junction Boxes

Example: **NLOPAC-R6T2427BZ** = 6" AC T24 Opal, 1050lm / 16W, 2700K, Bronze finish