
Mini-puck



Complete flexibility is now available with our mini LED pucks. Feel free to recess, surface mount or direct this warm LED light to attain your desired lighting effect.



Model	Size	Watts	Delivered lumens	LED lumens	CRI	Color °T	Voltage
LEDRDM1	Ø2"	1 W	80 lm	90 lm	80	3000 K	12 V

Specifications

12V DC LED driver required
 Over 50,000 hours of service life
 12" input lead with quick connector
 24" interconnection harness included
 Warm white light output
 Excellent color rendering
 Superior LED performance and lifespan
 Smooth 360° wide spread
 Minimal heat emission
 Surface adapter included
 Frosted lens
 Aluminum construction
 Gimbal LED module
 Refer to website for dimmer compatibility
 5-year warranty
 Kits available

Note

Plug-in or hard-wired power supply required for installation. Sold separately.

Other Color °T and Finishes available, but may require MOQ's and longer lead times. Please contact your DALs representative for more information.

Finish

● **SBA** Sandblasted aluminum

Power supplies: plug-in

ETR-LED10WPI
 12VDC/10W class 2 LED driver
ETR-LED24WPI
 12VDC/24W class 2 LED driver

Power supplies: hard-wired

BT06DIM-IC
 6W dimmable LED hardwire driver
BT12DIM-IC
 12W dimmable LED hardwire driver
BT24DIM-IC
 24W dimmable LED hardwire driver
BT36DIM
 36W dimmable LED hardwire driver
BT48DIM
 48W dimmable LED hardwire driver

Accessories

4000-E24
 24" extension cord
4000-E60
 60" extension cord
4000HRNS-24
 24" interconnection harness

Order example

LEDRDM1-SBA
 LEDRDM1 single puck with a 1W LED array with 80 lumens at 3000K in a sandblasted aluminum finish

