



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11650 - 9 Watt 2 Foot T5 LED; CCT Selectable; G5 Base; Type B; Ballast Bypass; Single or Double Ended Wiring; White Finish; 120-277 Volt

- CCT Selectable



ELECTRICAL

Technology:	LED
Watts:	9W
Volts:	120V-277V
Lumens:	1100L/1175L/1200L/1250L/1150 L
CRI:	82
CCT (Kelvins):	3000K/3500K/4000K/5000K/6500K -
Beam Spread :	160
Hours Rated:	50000
Incandescent Equivalent :	75W
Fluorescent Equivalent :	14W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Lamp End Type :	Single Ended; Double Ended
THD:	<25%
Power Factor :	>0.9
Light Source:	LED
Voltage Type:	Range Voltage
Warranty:	5 Year Limited - T5 LED Bulbs - Ballast Bypass

PACKAGING

Each UPC:	045923116506
Each Quantity:	1
Each Dimensions:	21.65 x 0.87 x 0.87

PHYSICAL

Base:	Miniature Bi Pin
Shape:	T5
Finish:	White
Lens Finish:	Frost
Lens Material:	Glass
Dimensions (In.):	MOL: 0.88 - MOD: 0.88
Nominal Length:	24
Weight (Lbs.):	0.2
Material:	Plastic
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Classified; cETLus - Listed; cRUus - Recognized Component
Location Rating:	Damp
Indoor/Outdoor:	Indoor
Energy Star Qualified:	No
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
IP Rating:	IP20
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions

INFO

Installation Note:	Not for use in vapor tight fixtures.
Shatterproof Type:	PET Coated
Tube Guard Use:	No