



Project/Job Name: _____
 Location: _____
 Fixture Type: _____
 Notes: _____



S11756 - 24/32/40 Wattage Selectable; 8 Foot T8 LED;
 30/35/40/50/65K CCT Selectable; 120-277 Volt; FA8 Base

- Wattage Selectable
- CCT Selectable



ELECTRICAL

Technology:	LED
Watts:	24W/32W/40W
Volts:	120V-277V
Lumens:	3500L/4400L/5500L
CRI:	82
CCT (Kelvins):	3000K/3500K/4000K/5000K/6500K - Soft White to Daylight
Beam Spread :	210
Hours Rated:	50000
Incandescent Equivalent :	100W
Fluorescent Equivalent :	40W/55W/70W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Type B Ballast Bypass
Lamp End Type :	Double Ended
THD:	20%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	Range Voltage
Warranty:	5 Year Limited - T8 LED Bulbs - Ballast Bypass

PACKAGING

Each UPC:	045923117565
Each Quantity:	1
Each Dimensions:	48.39 x 6.50 x 7.44

INFO

Installation Note:	Not for use in vapor tight fixtures. Must use both sections; Provided support clips may differ from current PI Sheet (SN1394). Please refer to the Instruction Sheet provided in the master carton or downloaded from the website, https://www.satco.com/s
Min Compartment Size:	Length: 96.06 in. Width: 10.63 in. Height: 2.76 in.
Shatterproof Type:	PET Coated
Includes:	(20) R17d Base Adapters and (10) Fastening Clips included per case

PHYSICAL

Base:	Single Pin
Shape:	T8
Finish:	White
Dimensions (In.):	MOL: 1 - MOD: 1
Nominal Length:	96
Weight (Lbs.):	0.98
Material:	Glass

COMPLIANCE

Safety Listing:	cULus - Classified; cRUus - Recognized Component
Location Rating:	Damp
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-HPN8SY
BAA Compliant:	No
Enclosure Rating:	Both
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions