



Project/Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**65-771R3** - Wattage 150W/175W/200W and CCT Selectable  
3K/4K/5K LED UFO High Bay; 120-347 Volt; Black Finish

- Wattage Selectable
- CCT Selectable



### ELECTRICAL

Technology:	LED
Watts:	150W/175W/200W
Volts:	120V-347V
Lumens:	28600L-32000L
Lamp Base :	Integrated
Lamp Shape :	Integrated LED
CRI:	80
CCT (Kelvins):	3000K/4000K/5000K
Color Description:	Warm White to Natural Light
Beam Spread :	90
Hours Rated:	50000
Dimmable:	Yes-Dimmable
DimmableText:	0-10V Dimming Only
Incandescent Equivalent :	1000W/1500W/2000W
HID Equivalent :	400W-450W
Operating Temperature :	-40C (-40F) to +50C (+122F)
Lamp Included :	Integrated
Replaceable Light Source :	No
Number of LEDs :	640
Surge Protection :	Built-in surge protection - 6KV
THD:	15%
Power Factor :	0.9
Warranty:	5 Year Limited - Fixtures

### PACKAGING

Each UPC:	045923651908
Each Quantity:	1
Each Dimensions:	14.17 x 14.17 x 4.92
Case UPC:	10045923651905
Case Quantity:	1
Case Dimensions:	14.17 x 14.17 x 4.92

### PHYSICAL

Finish:	Black
Lens Finish:	Clear
Lens Material:	Polycarbonate (PC)
Finish Family:	Black
Dimensions:	H:7.30" DIA:13.40"
Weight (Lbs.):	6.42
Material:	Die-cast Aluminum
Sensor:	Optional Add-On

### INSTALLATION

Wire Length:	72 in.
--------------	--------

### COMPLIANCE

Safety Listing:	cULus - Listed
Location Rating:	Wet
Indoor/Outdoor:	Indoor
DLC Approved:	Yes
DLC Classification:	Premium
DLC ID:	S-PQ3SZK
DLC Primary Use:	High-Bay Luminaires for Commercial and Industrial Buildings
UL/ETL Standard:	UL 1598; CSA-C22.2 No. 250.0
CA Prop 65:	Lead
BAA Compliant:	No
FCC Compliant:	Yes
IP Rating:	IP65
IK Rating:	IK08
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions

### INFO

Installation Note:	
Includes:	Mounting Height: Up to 20 feet Locking Hanging Hook; 6 Foot Whip

