

PRODUCT DETAILS:

Wattage settings includes: 3W (260 Lumens), 5W (350 Lumens), 8W (475 Lumens), 12W (750 Lumens)

- Three lens options offer versatility in beam spread via an easy to remove and insert assemble includes: 20° Spot, 40° Flood, 60° Flood
- Suitable for use in wet (outdoor direct rain) locations as defined by NEC and CEC. Meets
 United States UL Underwriters Laboratories & CSA Canadian Standards Association Product
 Safety Standards
- Photometrics based off engine photometrics.
- Incorporates CREE LEDs with application performance tested by CREE
- PVC constructed concrete pour kit and burial sleeve are supplied
- Optional performance lenses available
- For more information on how to control your landscape lighting via the Hinkley Home Automation App, click here.

WELL LIGHT

15705MZ-LMA27K

VARIABLE OUTPUT LED 2700K GRILL TOP

DETAILS	
FINISH:	Matte Bronze
MATERIAL:	Aluminum
GLASS:	Clear Lens
DIMMABLE:	No

DIMENSIONS	
WIDTH:	4.8"
HEIGHT:	4.8"
DEPTH:	4.8
WEIGHT:	3lb

LIGHT SOURCE	
LIGHT SOURCE:	LumaCore
LED NAME:	30G4SE-12W
VOLTAGE:	12v
VOLT AMPS:	12.4,3.2,5.3,7.8
COLOR TEMP:	3000
CRI:	80
INCANDESCENT EQUIVALENCY:	1 x 60w, 45w, 35w, 25w
DIMMABLE:	No

MOUNTING	
LEAD WIRE:	1 X 96"

SHIPPING	
CARTON LENGTH:	7
CARTON WIDTH:	7
CARTON HEIGHT:	13.5
CARTON WEIGHT:	4.5



PHONE: (440) 653-5500

Toll Free: 1 (800) 446-5539