## TAURUS Outdoor 3-774-15



| FIXTURE TYPE |      |
|--------------|------|
| PROJECT      | DATE |





-15 Black (Lit)

-15 Black

| LIGHT SOURCE                   | (1x) 10W LED with Driver on board, 3000K, CRI 90   |                   |                                    |
|--------------------------------|--|-------------------|------------------------------------|
| LUMINAIRE POWER                | 11.6W Input Power  |                   |                                    |
| RATED LIFE                     | 30000 hr RL  |                   | Ext.                               |
| OPTIONAL COLOR<br>TEMPERATURES | 3000K Only   |                   |                                    |
| LUMEN OUTPUT                   | Delivered: 190 lm (LM-79)  |                   | o                                  |
| INPUT VOLTAGE                  | 120V AC, 50/60Hz   |                   | H H                                |
| DIMMING                        | TRIAC Dimming 100-10%  |                   |                                    |
| CONSTRUCTION                   | Cast Aluminum Housing  |                   |                                    |
| DIFFUSER                       | - Clear Bubble Crystal Glass   |                   |                                    |
| FINISHES                       | Black (-15)  |                   |                                    |
| MOUNTING                       | 4" Octagonal J-Box<br>(Installer must provide a bead of caulk between<br>fixture housing and mounting surface) | DIMEN<br>W:<br>H: | 6.75″<br>18.00″                    |
| STANDARDS                      | cETL Wet listed, Conforms to UL STD 1598,<br>Certified CAN/CSA STD C22.2 No 250.0.                             | Ext:<br>M.C:      | 6.75"<br>6.00" From top of fixture |
|                                |  |                   |                                    |

Order example for standard fixture: 3-774-15 (x-xxx: LED Sequence # / -xx: Finish)

