## **LED Vanity Lamp**



## START FROM HERE


- Make sure **POWER** is **COMPLETELY OFF** at the fuse box
- Have your fixture installed by a qualified licensed electrician
- · Prepare everything in a clear area
- · Wear gloves at all time during this installation
- · Read instructions carefully before you start assembly
- · Keep this installation sheet for future reference

**Technical Support:** 1-855-855-8926

## Please Note:

- This Kuzco LED fixture comes with pre-wired LED module(s)
- Unless instructed, Do Not touch any part of the LED module(s) as any unnecessary contact with the module could cause permanent damage
- Use ELV (Electronic Low Voltage) type of dimmer for dimming application
- 1. Remove the fixture from its original packaging. First remove the set screws (2d) from the side of the lamp cover (2e) using the allen key provided. Now remove the mounting plate (1c) from the backplate (2b) by removing the round nuts (2c). Attach the mounting plate (1c) to the electrical junction box (1a), using the screws (1d) provided. in the hardware package.
- 2. Attach the backplate (2b) to the mounting plate (1c). First attach all wiring with the provided marrets (2a) (white to white "N", black to black "L", ground to ground "G"). Push the fixture backplate (2b) onto the mounting plate (1c), then thread the round nuts (2c) into the mounting plate studs (1b). Next, place the lamp cover (2e) over the backplate (2b) and secure with set screws (2d).
- To prevent moisture from entering the outlet box and causing a short, seal around the top and side perimeter between the fixture and the wall surface with weather resistant caulking (see illustration 1). The space at bottom should be left un-caulked to prevent moisture build-up. Apply a small amount of weather resistant caulking around the side perimeter between the cap nut and mounting plate.

## Illustration 1



You have now completed the installation of your fixture, please enjoy.

