



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

Ash LED Sconce ASHS Series

Features

Metal perforated design that casts interesting light pattern on wall. Ideal use in hallways, entrances or anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Meets ADA requirements. Fixture mounts to standard junction box (not included).

Construction

Back plate is die-formed of 22-gauge steel. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

Exterior metal parts are powder coated in black with inner gold finish.

Diffuser

White acrylic diffuser.

Electrical

This unit is direct wired with a constant current LED driver rated for 120-277V VAC input, 0-10V dimmable.

Lamping

Integrated LED modules capable of producing:
15W = 780 source lumens
3000K (CCT). Rated for 50,000 Hrs., 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations.
ADA

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions
subject to change without notice.

Ordering Information:

Black	LED	Source Lumens	CCT	H	W	D
ASHS0414L30D2BK	15W	780	3000K	13-5/8"	4-3/4"	3-3/4"

