

FRAME

Wall/ceiling mounted • Damp location listed



Specifications:

P350025-009-30

Description:

One-light Small LED Flush Mount Sconce (8")

Construction:

Brushed Nickel (-009)
 Steel
 Glass: Canyon Stone
 LED Module is replaceable (part # 93074039)
 Dimming to 10% brightness with most ELV type dimmers
 (See Dimming Notes)
 6" of wire supplied

Images:



Dimensions:

Square: 9"
 Height: 2-1/4"

Performance:

Number of Modules	1
Input Power	17W
Input Voltage	120V
Input Frequency	60Hz
Lumens/LPW	1276/73 (LM-79) per module
CCT	3000K
CRI	90+
Life	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30° C
Max. Operating Temp	30° C
Warranty	5 year warranty
Labels	cCSAus Damp location listed ENERGY STAR® qualified

Catalog number:

Base	Finish	Color Temp
P350025	009 - Brushed Nickel	30

Dimming Notes:

P350025 is designed to be compatible with both Triac and Electronic Low Voltage (ELV-Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls:

Electronic Low Voltage ELV Reverse Phase Controls

Lutron	Diva	DVELV-300P
Lutron	Caseta	
Lutron	Nova T	NTELV-300
Leviton	SureSlide	6672
Lutron	Ariadni	AY-600P
Leviton	Illumatech	IPlo6-1LZ
Leviton	SureSlide	6674
Pass & Seymour	Harmony	DCL453PTCCCV6
Lutron	Ariadni	AYLV-600P
Lutron	Nova T	NTLV-600
Lutron	Maestro	MAELV-600
Lutron	Spacer system	SPSELV-600
Lutron	Ariadni	AYCL-153P
Lutron	Skylark Contour	CTCL-153P
Lutron	Diva	DVCL-153P
Lutron	Toggler	TGCL-153P
Lutron	Maestro	MACL-153M
Lutron	Ariadni	AYLV-600P
Lutron	Maestro	MA-600
Lutron	Renoir II	AWRMG-EAW

Digital type dimmers are not recommended.

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.