

Project:

# Intervals Linear Beam Pendant Spec Sheet


SKU: 20QWS04C Learn more at:

https://sonnemanlight.com/intervals-linear-beam-pendant

Description: Intervals is a uniquely integrated linear architectural lighting system of rhythmically aligned bidirectional illumination, with a range of available decorative and functional trims. Architecturally scaled, the suspended horizontal beams span long lengths within a space, supported from ceiling-mounted cables or stems, forming a dramatically powerful approach to illuminating architecturally expansive locations. SONNEMAN's new <a href="INTERVALS Recessed Downlights">INTERVALS Recessed Downlights</a> extend and support these Intervals Linear Beam Pendants. Together, they achieve a comprehensive and unified approach to dynamically lighting interior spaces.

Type #:





# **Dimensions**

 Height:
 11.5"

 Width:
 56"

 Length:
 56"

 Canopy/Backplate/Base:
 4.5"

 Hanging Details:
 10'

 Adjustable Cable

 Size:
 4' x 4'

# Electrical Specs

Bulb(s) Included?: Yes Bulb 1 Type: Integral LED **Bulb Quantity:** 12 Input Voltage: 120-277VAC Wattage: 56 Initial Lumens: 17320 Color Temperature: 3000K CRI: 90 Power Supply Type: Driver Power Supply Quantity: Power Supply Location: Fixture Dimming Type: TRIAC & ELV @120V / 0-10V

#### Installation

Installation:

Licensed electrician required

Sloped Ceiling Compatible?:

Minimum Hanging Height:

Maximum Hanging Height:

134.25"

#### Shade

Shade 1 Material: Glass
Shade 2 Material: Aluminum

### **Available Finishes**

Available Finishes: Satin Black w/Clear w/Cone Uplight Trim, Satin Black w/Etched Cylinder Uplight Trim, Satin White w/Clear w/Cone Uplight Trim, Satin White w/Etched Cylinder Uplight Trim

# **General Listings**

Features: Certification: Color/Finish:

Dark Sky Friendly:

Damp Rated C-ETL-US Satin White w/Etched Cylinder Uplight Trim

Uplig N