

TELSHOR Outdoor

120v : **3-710-2xx**

277v : **37-710-2xx**

oxygen

FIXTURE TYPE _____

LOCATION _____

PROJECT _____

DATE _____





-24 Satin Nickel



-22 Oiled Bronze

LIGHT SOURCE	1 x 10.1W LED, 3000K, CRI 90
LUMINAIRE POWER	12.9W at 120V
RATED LIFE	60000 hr RL
OPTIONAL COLOR TEMPERATURES	2700K, 3500K, 4000K
LUMEN OUTPUT	Delivered: 625 lm (LM-79)
INPUT VOLTAGE	120V or 277V
DRIVER OUTPUT	350 mA, 12W
DIMMING	0-10v & Phase (ELV) Dimming - 50/60Hz 100% to 10% Dimming
CONSTRUCTION	Cast Aluminium and Acrylic
DIFFUSER	-2 Matte White Acrylic
FINISHES	Oiled Bronze (-22), Satin Nickel (-24)
MOUNTING	4" Octagonal J-Box (Installer must provide a bead of caulk between fixture housing and mounting surface)
STANDARDS	ETL Wet, Conforms to UL STD 1598, Certified CAN/CSA, STD C22.2 No 250.0.



DIMENSIONS

W: 7.25"
H: 16.50"
Ext: 5.00"
M.C: 8.23" From top of fixture

Order example for standard fixture:

3-710-224 (x- Voltage - xxx-Sequence # - x-Diffuser - xx-Finish)

3: 120v, **37:** 277v

Order example for optional color temperatures: **3-710-27224**

27: 2700K, **35:** 3500K, **40:** 4000K

