

The Ash outdoor wall sconce is a modern take on the classic industrial-style light fixture. The Ash features a sleek metal shade and clear diffuser that creates a column of diffused light from under the shade. Ash wall sconces feature energy-efficient, fully dimmable integrated LED lamping. Available in four sizes (8", 10", 12", 16") and two finishes: Bronze and Charcoal.

Outstanding protection against the elements:

- Powder coat finishes
- Stainless Steel mounting hardware
- Impact-resistant, UV stabilized acrylic lensing
- IP-65 Rated

SPECIFICATIONS

DELIVERED LUMENS	619 or 1115 with clear cylinder 400 or 863 with clear lens
WATTS	8 or 18
VOLTAGE	Universal 120-277V, with integral transient 2.5kV surge protection (driver)
DIMMING	0-10, ELV
LIGHT DISTRIBUTION	Symmetric
MOUNTING OPTIONS	Wall
PERFORMANCE OPTIONS	Photocontrol / Surge Protector
CCT	2700K or 3000K
CRI	90+
COLOR BINNING	3 Step
BUG RATING	B0-U1-G0
DARK SKY	Compliant (Lensed version only)
WET LISTED	IP65
GENERAL LISTING	ETL
CALIFORNIA TITLE 24	Can be used to comply with CEC 2016 Title 24 Part 6 for outdoor use. Registration with CEC Appliance Database not required.
START TEMP	-30°C
FIELD SERVICEABLE LED	Yes
CONSTRUCTION	Aluminum
HARDWARE	Stainless Steel
FINISH	Powder Coat
LED LIFETIME	L70; 70,000 Hours
WARRANTY*	5 Years
WEIGHT	4 lbs.








ASH 12 shown in charcoal/clear lens

ORDERING INFORMATION

7000WASH	CRI / CCT	LENGTH	LENS	FINISH	VOLTAGE	OPTIONS	
	L927 LED LO-OUTPUT 90 CRI, 2700K	12 12"	C CLEAR CYLINDER	Z BRONZE	UNV 120V-277V UNIVERSAL		NONE
	H927 LED HI-OUTPUT 90 CRI, 2700K		D CLEAR LENS	H CHARCOAL		PC	BUTTON PHOTOCONTROL
	L930 LED LO-OUTPUT 90 CRI, 3000K					SP	SURGE PROTECTION
	H930 LED HI-OUTPUT 90 CRI, 3000K					PCSP	BUTTON PHOTOCONTROL & SURGE PROTECTION

^{*} Visit techlighting.com for specific warranty limitations and details.






PHOTOMETRICS*

*For latest photometrics, please visit www. techlighting.com/OUTDOOR

ASH 12 WITH CYLINDER

Total Lumen Output: 619
Total Power: 8
Luminaire Efficacy: 77
Color Temp: 3000K
CRI: 90
BUG Rating: B0-U1-G0



PROJECT INFO

FIXTURE TYPE & QUANTITY

JOB NAME & INFO

NOTES



