

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

## Stretch LED Swing Arm

Model & Size	Color Temp & CRI	Watt	LED Lumens	Delivered Lumens	Finish
BL-1630 1 Light	3000K 90	7.5W	489	260	BK Black
BL-1660 2 Light		17.2W	936	623	TT Titanium WT White

Example: **BL-1630-BK**

### DESCRIPTION

A contemporary utilitarian design. Stretch incorporates a rubberized flexible and fixable arm as part of this unique modern design. The die-cast aluminum head also serves as the heat sink for the powerful 7.5 watt LED.

### FEATURES


- A contemporary utilitarian design
- Flexible rubber tube for aiming
- Two 12" cord covers included
- Fingertip touch dimming on head
- Integral driver
- 8 foot cord included for hard-wired and portable installation
- Conversion plate for 4" junction box included
- Hold switch to dim
- Driver concealed within the canopy
- 5 year warranty

### SPECIFICATIONS

<b>Construction:</b>	Steel canopy, flexible tubing with die-cast aluminum head with etched glass diffuser
<b>Power:</b>	17.2W, 7.5W
<b>Input:</b>	100-240 VAC, 50/60Hz
<b>Rated Life:</b>	30000 Hours
<b>Mounting:</b>	Heavy gauge retention clips support trim firmly. Safety cabling standard.
<b>Finish:</b>	White, Black, Titanium
<b>Operating Temp:</b>	-4°F to 104°F (-20°C to 40°C)
<b>Standards:</b>	ETL, cETL, Damp Location Listed



### FINISHES



### LINE DRAWING

