

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

## Niveous Ceiling And Wall Mount 3000K

Model & Size	Color Temp & CRI	Watt	LED Lumens	Delivered Lumens	Finish
FM-W52306 6"	3000K 90	9.5W	800	680	WT White

Example: **FM-W52306-WT**

- For 277V special order, add an "F" before the finish: FM-W52309F-WT
- For alternate color temperature, special order adding -27 or -35: FM-W52309F-35-WT

### DESCRIPTION

Like the perfect snowball, unique yet wholly recognizable.

### FEATURES

- Spheres of pure light
- Mouth blown etched opal glass diffuser provides even illumination
- No transformer or driver required except 277V option (special order).
- 2700K /3500K for 6" and 9" options only (special order)
- ACLED driverless technology
- 5 Year warranty

### SPECIFICATIONS

Color Temp:	3000K
Input:	120 VAC, 50/60Hz
CRI:	90
Dimming:	ELV: 100-10%
Rated Life:	45000 Hours
Mounting:	Can be mounted on ceiling or wall in all orientations
Standards:	ETL, cETL, IP65, Title 24: 2019 Wet Location Listed
Construction:	Aluminum hardware with opal glass diffuser

### REPLACEMENT PARTS

RPL-GLA-52306 - Glass for FM-W52306




### FINISHES



White

### LINE DRAWING



Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

## Niveous Ceiling And Wall Mount 3000K

Model & Size	Color Temp & CRI	Watt	LED Lumens	Delivered Lumens	Finish
FM-W52309 9"	3000K 90	18W	1600	1428	WT White

Example: **FM-W52309-WT**

- For 277V special order, add an "F" before the finish: FM-W52309F-WT
- For alternate color temperature, special order adding -27 or -35: FM-W52309F-35-WT

### DESCRIPTION

Like the perfect snowball, unique yet wholly recognizable.

### FEATURES

- Spheres of pure light
- Mouth blown etched opal glass diffuser provides even illumination
- No transformer or driver required except 277V option (special order).
- 2700K /3500K for 6" and 9" options only (special order)
- ACLED driverless technology
- 5 Year warranty

### SPECIFICATIONS

Color Temp:	3000K
Input:	120 VAC, 50/60Hz
CRI:	90
Dimming:	ELV: 100-10%
Rated Life:	45000 Hours
Mounting:	Can be mounted on ceiling or wall in all orientations
Standards:	ETL, cETL, IP65, Title 24: 2019 Wet Location Listed
Construction:	Aluminum hardware with opal glass diffuser

### REPLACEMENT PARTS

RPL-GLA-52309 - Glass for FM-W52309




### FINISHES



White

### LINE DRAWING



Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

## Niveous Ceiling And Wall Mount 3000K

Model & Size	Color Temp & CRI	Watt	LED Lumens	Delivered Lumens	Finish
FM-W52312 12"	3000K 90	24W	2229	1900	WT White

Example: **FM-W52312-WT**

- For 277V special order, add an "F" before the finish: FM-W52309F-WT
- For alternate color temperature, special order adding -27 or -35: FM-W52309F-35-WT

### DESCRIPTION

Like the perfect snowball, unique yet wholly recognizable.

### FEATURES

- Spheres of pure light
- Mouth blown etched opal glass diffuser provides even illumination
- No transformer or driver required except 277V option (special order).
- 2700K /3500K for 6" and 9" options only (special order)
- ACLED driverless technology
- 5 Year warranty

### SPECIFICATIONS

Color Temp:	3000K
Input:	120 VAC, 50/60Hz
CRI:	90
Dimming:	ELV: 100-10%
Rated Life:	45000 Hours
Mounting:	Can be mounted on ceiling or wall in all orientations
Standards:	ETL, cETL, IP65, Title 24: 2019 Wet Location Listed
Construction:	Aluminum hardware with opal glass diffuser

### REPLACEMENT PARTS

RPL-GLA-52312 - Glass for FM-W52312



### FINISHES



White

### LINE DRAWING

