

Project:

Purolinear 360 LED Wall Bar Spec Sheet

SKU: 23QSKL222B120PHA Learn more at:
<https://sonnemanlight.com/purolinear-360-led-wall-bar>



Description: A system of linear tubes, set within the geometry of surface-mounted cylinder brackets, rotate individually to direct the LED illumination in 360 degrees along their axis. Arranged in a linear pattern or along a single path, the possibilities for compositions are endless and unlimited in scalability. Set on a wall, in line behind a bed, the rotatable luminaires provide the variability of direct or indirect illumination.

Type #:

Dimensions

| | |
|------------------------------|------------------|
| Height: | 1.25" |
| Width: | 49.25" |
| Extends: | 2.75" |
| Minimum Extension: | 2.75 |
| Maximum Extension: | 2.75 |
| Canopy/Backplate/Base: | 4.5" |
| Shape: | Double Linear |
| Size: | 24" |
| Canopy/Backplate/Base Depth: | 0.5 |

Electrical Specs

| | |
|------------------------|--------------|
| Bulb(s) Included?: | Yes |
| Bulb 1 Type: | Integral LED |
| Bulb Quantity: | 2 |
| Input Voltage: | 120VAC |
| Wattage: | 7 |
| Initial Lumens: | 1380 |
| Delivered Lumens: | 980 |
| Color Temperature: | 3000K |
| CRI: | 90 |
| Power Supply Type: | Driver |
| Power Supply Quantity: | 1 |
| Power Supply Location: | Outlet Box |
| Dimming Type: | TRIAC/ELV |
| Bulb Max Wattage: | 7 |

Installation

| | |
|---------------|-------------------------------------|
| Installation: | Licensed electrician required |
|---------------|-------------------------------------|

Shade

| | |
|-------------------|--------------------|
| Shade 1 Material: | Optical Acrylic |
|-------------------|--------------------|

Available Finishes

Available Finishes: Polished Chrome (.01),
Satin Black (.25), Satin Chrome (.23), Satin
White (.03)

General Listings

| | |
|--------------------|---------------------------------|
| Features: | ADA Compliant, Damp Rated |
| Certification: | C-ETL-US |
| Color/Finish: | Satin Black (.25) |
| Dark Sky Friendly: | N |