## DOUBLE ADJUSTABLE FLOOD LIGHT

### Endurance<sup>™</sup> - WP-LED529



5"

45°

max: 48%'

Æ

# WAC LIGHTING

Responsible Lighting®

Fixture Type:	
Catalog Number:	
Project:	
Location:	

#### **PRODUCT DESCRIPTION**

Die cast aluminum factory sealed luminaire with patent pending design for a water and dust proof IP66 rated outdoor.

#### FEATURES

- Rotate to continuously adjust beam angles indexed at  $15^\circ, 25^\circ, 40^\circ, 60^\circ$
- IP66 and ETL & cETL Wet Location Listed
- Factory-Sealed LED Light Engine
- Die-Cast Aluminum Construction
- 120V Direct Wire No Driver Needed
- Safety cable and canopy included
- Comes with extension rod kit to extend up to 44" total
- Detachable Shroud

**ORDER NUMBER** 

W D

- Safety cable recommended for extensions over 36"
- One 6", one 12", one 24" field interchangable rods included

#### SPECIFICATIONS

Construction: Die-cast aluminum Power: Line Voltage input (120V) CRI: 85 Dimming: 100% - 10% with Electronic Low Voltage (ELV) dimmer Finish: Architectural Bronze, Black, Graphite and White Operating Temp: -40°F to 122°F (-40°C to 50°C) Standards: IP66, Wet Location, ETL & cETL Listed Rated Life: 50,000 hours

	Power	Comparable	Beam	Delivered Lumens	СВСР	Color	<sup>,</sup> Temp	Finish	
VP-LED529	30W	150W x2	15° 60°	600 x2 985 x 2	4145 x 2 875 x 2	30	3000K		Architectural Bronze Architectural Black
Double	5000	PAR38	15° 60°	695 x 2 11402 x 2	4800 x 2 1015 x 2	40	4000K	AGH AWT	Architectural Graphite Architectural White

#### Example: WP-LED529-30-ABZ

**WAC Lighting** www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050 **Western Distribution Center** 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. FEB 2017