

Hilux

Dals' new high-powered recessed downlight is a go-to for your commercial projects. With its five color temperatures to choose from, a cast aluminum housing, high lumen output, and indoor/outdoor rating, this can be installed just about anywhere. From clinics to schools and hotels to boutiques, this is the only slim recessed fixture you will need.

NEW

WET LOW-GLARE IC RATED AIR TIGHT Intertek

2700k 3000k 3500k 4000k 5000k

COLOR TEMPERATURE

JA8 CERTIFIED

ENERGY STAR



Model	Size	Watts	Delivered lumens	LED lumens	CRI	Color °T	Voltage
HPD4-CC	4"	20 W	1415 lm	1555 lm	90	2700, 3000, 3500, 4000, 5000 K	120 V
HPD6-CC	6"	30 W	2100 lm	2310 lm			
HPD8-CC	8"	40 W	2600 lm	2850 lm			

Specifications

Every fixture includes a junction box with an integrated driver
 Over 50,000 hours service life
 Switch-selectable CCT: 2700 K/3000 K/3500 K/4000 K/5000 K
 Smooth 360° wide spread
 90° beam angle
 Cast aluminum construction
 Suitable for wet locations
 Compatible with TRIAC, ELV, and 0-10V dimmers (0-10V dimming only available on HPDx-V versions)
 Refer to website for dimmer compatibility
 IC certification (suitable for direct contact with insulation)
 Air-tight certified as per ASTM E283-04
 5-year warranty

Finish

- **BK** Black (HPD4 and HPD6 only)
- **WH** White

Options

HPD4-CC-V-XX

4" high-powered downlight with input for 0/10V, 120-277-347V

HPD6-CC-V-XX

6" high-powered downlight with input for 0/10V, 120-277-347V

HPD8-CC-V-XX

8" high-powered downlight with input for 0/10V, 120-277-347V

Accessories

RFP-UNI

Universal rough-in plate

RFP-46 (HPD4, HPD6)

Rough-in plate

RFP-58 (HPD8)

Rough-in plate

Order example

HPD6-CC-WH


Dimmable 6" high-powered commercial downlight in a white finish

Note

Other Color °T and Finishes available, but may require MOQ's and longer lead times. Please contact your DALI representative for more information.


HPD4-CC

Ø4 1/4" 



HPD6-CC

Ø6 1/2" 



HPD8-CC

Ø7 1/2" 