

# ASSEMBLY AND INSTALLATION INSTRUCTION

**WARNING :** Before starting installation, turn off power by turning off circuit breakers. Turning off the power by using the light switch is not sufficient to prevent electrical shock. If you feel you do not have electrical experiences needed, have the fixture installed by a qualified licensed electrician.

**CAUTION :** This is just an installation "guide ". Pls check with your local certified electrician for proper installation per your city code. We can not be held responsible for the use or misuse of the installation guide provided.

## Wiring :

1. Mount strap securely to the outlet box with 2 pcs of 5/32" mounting screws provided.
2. Pull junction box wires out .
3. Adjust the cord to your desired length through strain relief.
4. Attach junction box BK wire with driver RED wire ; junction box WH wire with driver BK wire with wire connectors provided.
5. Attach Cooper Grounding wire from canopy to the Green Grounding screw on the strap, make a round and connect junction box Green Grounding wire by wire connector provided.
6. Lay driver inside the canopy.
7. Pull the cord downward until the strain relief touches the strap.
- 8 Fix the canopy to strap by rotating 2 set screws till it is tight.
9. Lay the front of heat sink onto the opening hole of the glass, put a rubber ring and fix the glass on the front of heat sink by rotating diffuser until it is tight.
- 10. Turn on the power.**

