

Everlume

Wall or Ceiling Mounted • Damp Location Listed **PROGRESS LED**

Description:

Everlume Collection 1-Light Satin White Frosted Glass LED Modern Bath Vanity Linear Panel Light

Specifications:

- Frosted Polystyrene Diffuser
- Dimmable to 10% brightness (See Dimming Notes)
- Frame covers a standard 4" recessed outlet box: 17.72 in W., 0.78 in ht., 4.37 in depth
- Mounting backplate for outlet box included
- 6 in of wire supplied
- Americans With Disabilities Act (ADA) compliant

Performance:

Number of Modules	1
Input Power	32 W
Input Voltage	120 VAC
Input Frequency	60 Hz
Lumens/LPW (Delivered)	2,808/87 (LM-79)
CCT	3000 K 4000 K
CRI	90 CRI
Life (hours)	60000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Warranty	5-year Limited Warranty
Labels	cCSAus Damp Location Listed Meets California Title 24 JA8-2019

P300306-028-CS



Dimensions:

Length: 32.01 in
 Extends: 1.38 in
 Height: 5 in
 H/CTR: 2-1/2 in

Frosted Polystyrene Diffuser
 Width: 0.39 in
 Height: 4 in

P300306-028-CS

Dimming Notes:

P300306-028-CS is designed to be compatible with many Triac/Forward Phase ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls:

Eaton AAL06

Eaton SAL06P

Leviton 6672

Leviton 6674

Lutron DVELV-300P

Lutron DVCL-253P

Lutron Caseta Wireless

Lutron MACL-153M

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.