


Project:

## Thin-Line LED Wall Bar Spec Sheet

SKU: 2812.25-6    Learn more at:  
<https://sonnemanlight.com/thin-line-led-wall-bar>

Description:

**A system of minimally scaled LED uplight/downlight wall bars, indirect light wall bars, and pendants**, Thin-Line is offered in a variety of lengths, finishes, and lighting configurations. One-sided configurations direct light in a single direction, and can be mounted in an uplight or downlight orientation. Two-sided configurations direct light both up and down.



Type #:

### Dimensions

Height:	1"
Width:	72"
Extends:	3.5"
Minimum Extension:	3.5"
Maximum Extension:	3.5"
Size:	6' Two-Sided
Canopy/Backplate/Base Width:	1
Canopy/Backplate/Base Height:	1

### Electrical Specs

Bulb(s) Included?:	Yes
Bulb 1 Type:	Integral LED
Bulb Quantity:	2
Input Voltage:	120VAC
Wattage:	72
Initial Lumens:	4440
Delivered Lumens:	2700
Color Temperature:	3000K
CRI:	90
Power Supply Type:	Driver
Power Supply Quantity:	2
Power Supply Location:	Remote
Dimming Type:	TRIAC/ELV
Bulb Max Wattage:	72

### Installation

Installation:	Licensed electrician required
Installation Orientation:	Any Orientation

### Shipping

Carton 1 L x W x H:	75" X 7" X 4"
Carton 1 Gross Weight:	7 LBS

### Shade

Shade 1 Material:	Aluminum w/Optical Acrylic
-------------------	----------------------------

### Available Finishes

Available Finishes: Bright Satin Aluminum (.16), Satin Black (.25), Satin White (.03)

### General Listings

Features:	Damp Rated
Certification:	cETL
Color/Finish:	Satin Black (.25)
Dark Sky Friendly:	N