

Assembly Instruction Sheet #S-9935P19 For Style 9935P19

Tools Required: Flathead screwdriver, Phillips screwdriver, pliers, wire cutters, wire strippers, electrical tape, safety glasses.
Light Source: (9) E12 Candelabra Base Bulbs 60W Maximum (not included).
Estimated Assembly Time: 20-30 minutes
Preparation: Identify and impact all parts before beginning installation. Check package content list and diagrams below to be sure all parts are present. If any parts are missing or damaged, do not attempt to assemble, install, or operate the fixture. Contact customer service for replacement parts.

Warnings and Cautions
 Turn off electricity at circuit breaker or main fuse box before installation. Consult a licensed electrician if in doubt. These instructions are provided for your safety. It is very important you read them completely before installing the fixture. We strongly recommend that a licensed, professional electrician perform the installation. Disconnect fixture from power source before replacing bulbs. Make sure bulbs are given sufficient time to cool before removal.

Package Contents



A Fixture Body x1 **D** Ceiling Canopy x1



B The bottom part x1



C The top part x1

Hardware Contents

PART	DESCRIPTION	QUANTITY
BB	Wire nut	2pcs
EE	Outlet Box Screw	2pcs
BB		
EE		



STEP 1 - Install metal part to Fixture Body .




Figure 1

STEP 2 - Install the Canopy Chain Loop and Nipple




Figure 2

STEP 3 - Install the Fixture Chain and Ceiling Canopy




Figure 3

STEP 4 - Wire Connections

All the standard wire connectors (not included) to make all wire connections. Twist connectors and wires are tightly joined together. Wrap each connection with approved electrical tape and carefully stuff all the connected wires into the Outlet Box.




Figure 4

STEPS - Install Bulbs.




Figure 5