

# FX-3669-5 INSTALLATION SHEET

## IMPORTANT SAFETY INSTRUCTIONS:

\* These instructions are provided for your safety. It is very important that they are read completely before beginning the installation of your fixture.

\* DIRECT WIRE FIXTURES: WE STRONGLY RECOMMEND INSTALLATION BY A LICENSED ELECTRICIAN.

## TO ASSEMBLE:

Shut off the main electrical supply at fuse box/circuit breaker.

1. Loosen the set screw (2).
2. Put the wire (1) through the canopy and the mounting bar, leave desired length of wire outside the canopy and lock it with plastic ring and set screw (2).
3. Connect the ground wires "⏚", Cathode wire "N", Anode wire "L" to the supply wire in the junction box as illustrated (3).
4. Affix mounting bar to junction box using mounting screws (4).
5. Affix canopy (5) to mounting bar using knob (6).
6. Install the bulb (not included) (7).

Turn on power and enjoy!!!

**Use 60WX5 Max type A BULB (Bulb not included)**

## WARNINGS:

Turn off power (unplug from the wall outlet) before replacing the bulb(s), making sure the bulb(s) have sufficient time to cool down.

Do not subject the lighting fixture to any shock while lit as shattering of bulbs may result.

To avoid risk of fire, do not exceed the recommended wattage.

## CARE INSTRUCTIONS:

To clean, use a soft cloth only. DO NOT use any chemical or abrasive cleaners.

★ Keep this instruction for future reference

