

WAC LIGHTING

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Quick Connect™

4.5" Sloped Ceiling Pendant Canopy, Transformer Included

Model & Wattage	Lumens	Color Temp & CRI	Finish
QMP-S60ERN Max 60W			BN Brushed Nickel CH Chrome

Example: **QMP-S60ERN-BN**

FEATURES


- For use with any of our Quick Connect pendants
- 60W integral electronic transformer included
- Smooth and continuous ELV dimming
- Mounts over a standard 4" junction box
- Includes optional decorative collar for shallow junction box
- Swivels up to 45° in either direction
- 5 year warranty

SPECIFICATIONS

Construction:	Plated aluminum
Power:	Max 60W
Input:	120 VAC, 50/60Hz
Finish:	Electroplated Brushed Nickel, Electroplated Chrome
Standards:	UL, cUL, Dry Location Listed



FINISHES



Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Ingo

Quick Connect™ Pendant 3000K

Model & Wattage	Lumens	Color Temp & CRI	Finish
QP-913LED	330		CF/BN Clear Frosted/Brushed Nickel
QP913			CF/CH Clear Frosted/Chrome

Example: **QP-913LED-CF/BN**

DESCRIPTION

Mouth blown handcrafted pendants inspired by dripping ice crystals and other elements of winter, Ingo features the clean design of mouth blown German art glass for an elegant statement.

FEATURES


- All socket sets include 6ft wire that may be cut in the field
- Lamp included
- Free of projected heat, ultraviolet and infrared radiation
- 5 year warranty

SPECIFICATIONS

Construction:	Mouth blown glass shade with plated metal hardware, Mouth blown glass shade with electroplated metal hardware
Input:	12 VAC, 50/60Hz
Dimming:	ELV: 100-15%
Light Source:	Xenon Bi-Pin Max 50W, LED Bi-Pin 2.7W, 110lm, 3000K, 85CRI
Rated Life:	30000 Hours
Finish:	Clear Frosted/Brushed Nickel, Clear Frosted/Chrome
Standards:	UL, cUL, Dry Location Listed
Operating Temp:	-4°F to 104°F (-20°C to 40°C)



FINISHES



Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Tulum

Quick Connect™ Pendant 3000K

Model & Wattage	Lumens	Color Temp & CRI	Finish
QP-914LED	235		FR/BN Frosted/Brushed Nickel
QP914			FR/CH Frosted/Chrome

Example: **QP-914LED-FR/BN**

DESCRIPTION

A frosted glass pendant carefully etched and paneled to reveal the mini pendant's inner light, Tulum offers a visually soft option for a contemporary space using a modern design that is perfect above a counter, bar or table.

FEATURES


- All socket sets include 6ft wire that may be cut in the field
- Lamp included
- Free of projected heat, ultraviolet and infrared radiation
- 5 year warranty

SPECIFICATIONS

Construction:	Mouth blown glass shade with plated metal hardware, Mouth blown glass shade with electroplated metal hardware
Input:	12 VAC, 50/60Hz
Dimming:	ELV: 100-15%
Light Source:	Xenon Bi-Pin Max 50W, LED Bi-Pin 2.7W, 110lm, 3000K, 85CRI
Rated Life:	30000 Hours
Finish:	Frosted/Brushed Nickel, Frosted/Chrome
Standards:	UL, cUL, Dry Location Listed
Operating Temp:	-4°F to 104°F (-20°C to 40°C)



FINISHES



Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Tikal

Quick Connect™ Pendant 3000K

Model & Wattage	Lumens	Color Temp & CRI	Finish
QP-915LED	235		CF/BN Clear Frosted/Brushed Nickel
QP915			CF/CH Clear Frosted/Chrome

Example: **QP-915LED-CF/BN**

DESCRIPTION

Mouth blown handcrafted pendants inspired by dripping ice crystals and other elements of winter, Ingo features the clean design of mouth blown German art glass for an elegant statement.

FEATURES


- All socket sets include 6ft wire that may be cut in the field
- Lamp included
- Free of projected heat, ultraviolet and infrared radiation
- 5 year warranty

SPECIFICATIONS

Construction:	Mouth blown glass shade with plated metal hardware, Mouth blown glass shade with electroplated metal hardware
Input:	12 VAC, 50/60Hz
Dimming:	ELV: 100-15%
Light Source:	Xenon Bi-Pin Max 50W, LED Bi-Pin 2.7W, 110lm, 3000K, 85CRI
Rated Life:	30000 Hours
Finish:	Clear Frosted/Chrome, Clear Frosted/Brushed Nickel
Standards:	UL, cUL, Dry Location Listed
Operating Temp:	-4°F to 104°F (-20°C to 40°C)



FINISHES



Clear
Frosted/
Brushed
Nickel

Clear
Frosted/
Chrome

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Clarity

Quick Connect™ Pendant 3000K

Model & Wattage	Lumens	Color Temp & CRI	Finish
QP-LED916	330		CL/BN Clear/Brushed Nickel
QP916			CL/CH Clear/Chrome

Example: **QP-LED916-CL/BN**

DESCRIPTION

Lovingly created by hand by Germany's finest glass blowers, the Clarity art glass pendant demonstrates dazzling spectral properties and can be mounted for use on track, rail or canopies.

FEATURES

- All socket sets include 6ft wire that may be cut in the field
- Lamp included
- Free of projected heat, ultraviolet and infrared radiation
- 5 year warranty

SPECIFICATIONS

Construction:	Mouth blown glass shade with plated metal hardware, Mouth blown glass shade with electroplated metal hardware
Input:	12 VAC, 50/60Hz
Dimming:	ELV: 100-15%
Light Source:	Xenon Bi-Pin Max 50W, Integrated LED 4W, 330lm, 3000K, 85CRI
Rated Life:	30000 Hours
Finish:	Clear/Brushed Nickel, Clear/Chrome
Standards:	UL, cUL, Dry Location Listed
Operating Temp:	-4°F to 104°F (-20°C to 40°C)



FINISHES



Clear/
Brushed
Nickel



Clear/
Chrome

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Bullet

Quick Connect™ Pendant 3000K

Model & Wattage	Lumens	Color Temp & CRI	Finish
QP-LED966	330		BN/BN Brushed Nickel
QP966			CH/CH Chrome

Example: **QP-LED966-BN/BN**

DESCRIPTION

Modern minimalist form derived from function, Bullet pendants are available in two hardware matching metal finishes. The white interior of the shade reflects light onto the surface below.

FEATURES


- All socket sets include 6ft wire that may be cut in the field
- Lamp included
- Free of projected heat, ultraviolet and infrared radiation
- 5 year warranty

SPECIFICATIONS

Construction:	Aluminum Shade with plated metal hardware, Aluminum Shade with electroplated metal hardware
Input:	12 VAC, 50/60Hz
Dimming:	ELV: 100-15%
Light Source:	Xenon Bi-Pin Max 50W, Integrated LED 6.4W, 450lm, 3000K, 85 CRI
Rated Life:	30000 Hours
Finish:	Brushed Nickel, Chrome
Standards:	UL, cUL, Dry Location Listed
Operating Temp:	-4°F to 104°F (-20°C to 40°C)



FINISHES



Brushed Nickel

Chrome

WAC LIGHTING

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Uber

Quick Connect™ Pendant 3000K

Model & Wattage	Lumens	Color Temp & CRI	Finish
QP-LED315 5W	180	3000K 85	PT/BN Platinum/Brushed Nickel PT/CH Platinum/Chrome

Example: **QP-LED315-PT/BN**

DESCRIPTION

Discover soft sparkling secrets by peering through the blades of Uber, a brilliantly accented LED pendant with a glimmering translucent diffuser that gently reveals light through distinctive Die-cast metal lines.

FEATURES


- All socket sets include 6ft wire that may be cut in the field
- Free of projected heat, ultraviolet and infrared radiation
- 5 year warranty

SPECIFICATIONS

Construction:	Metal pendant with electroplated metal hardware
Power:	5W
Input:	12 VAC, 50/60Hz
Dimming:	ELV: 100-15%
Light Source:	Integrated LED
Rated Life:	50000 Hours
Finish:	Electrostatically Powder Coated Platinum/Brushed Nickel, Platinum/Chrome
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL, cUL, Dry Location Listed



FINISHES



Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Genesis

Quick Connect™ Pendant 3000K

Model & Wattage	Lumens	Color Temp & CRI	Finish
QP-LED311 5W	210	3000K 85	BN/BN Brushed Nickel

Example: **QP-LED311-BN/BN**

DESCRIPTION

With dual uplight and downlight LED engines, Genesis integrates high performance with ambient lighting. An evolutionary design in a diminutive size resulting in a stunning decorative accent.

FEATURES

- All socket sets include 12ft wire that may be cut in the field
- Free of projected heat, ultraviolet and infrared radiation
- 5 year warranty

SPECIFICATIONS

Construction:	Solid Clear Seeded Glass with electroplated metal hardware
Power:	5W
Input:	12 VAC, 50/60Hz
Dimming:	ELV: 100-15%
Light Source:	Integrated LED
Rated Life:	50000 Hours
Finish:	Electroplated Brushed Nickel
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL, cUL, Dry Location Listed



FINISHES



Brushed Nickel