

WAC LIGHTING

Dune 826

Low Voltage Track Luminaire

System Type & Voltage	Model & Wattage	Finish
-HHT H Track - 120 VAC	826 50W	BK Black
-JHT J/J2 Track - 120 VAC	826L 75W	BN Brushed Nickel
-LHT L Track - 120 VAC		WT White

Example: **HHT-826-BK**

DESCRIPTION

Dune is a unique spot light with solid construction and simple aiming features for easy adjustments. Low Voltage track fixture offered in a wide variety of styles and finishes for a multitude of lighting applications in residential, retail, commercial and hospitality environments. Available in H, J/J2, and L style track configurations. Built-in transformer has a 1W minimum load and can be installed with an LED lamp.

FEATURES

- Available with LED lamp option
- 350° horizontal rotation and 90° vertical tilt
- Loop back aiming arm for simple adjustments
- Screw on lens cap
- Clear lens included
- Transformer concealed within the fixture
- 5 year warranty


SPECIFICATIONS

Construction:	Die-cast aluminum track head with polycarbonate transformer case and track adapter. Bi-pin ceramic socket for MR16 lamp., Die-cast aluminum fixture with polycarbonate track adapter. Heat resistant rubber grips over rear socket assemblies. Ceramic bi-pin sockets.
Power:	75W, 50W
Input:	120 VAC, 50/60Hz
Dimming:	ELV: 100-15%
Light Source:	MR16 (Order separately)
Finish:	Body Electrostatically powder Coated White, Electroplated Brushed Nickel, Body Electrostatically powder Coated Black
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL, cUL, Dry Location Listed


Fixture Type: _____
 Catalog Number: _____
 Project: _____
 Location: _____



FINISHES



LINE DRAWING



Fixture Type: _____

Catalog Number: _____







Project: _____

Location: _____

Dune 826

Low Voltage Track Luminaire

ACCESSORIES

	<i>Model</i>	<i>Description</i>	<i>Finish</i>
	LENS-16-AMB LENS-16-BLU LENS-16-GRN LENS-16-RED	<i>Colored Lens</i> <i>Colored Lens</i> <i>Colored Lens</i> <i>Colored Lens</i>	<i>Amber</i> <i>Blue</i> <i>Green</i> <i>Red</i>
	LENS-16-FR	<i>Clear/Frosted Lens</i>	<i>Frosted</i>
	LENS-16-SPR	<i>Spread Lens</i>	<i>Spread Lens</i>
	LENS-16-UVF	<i>UV Filter lens</i>	<i>Clear</i>
	LENS-16-BEL	<i>Beam Elongating Lens</i>	<i>Beam Elongating</i>
	LENS-16-HCL	<i>Honeycomb Louver</i>	<i>Black</i>