

CALYPSO Outdoor

120v : **3-730-xx**

277v : **37-730-xx**

oxygen

FIXTURE TYPE _____

LOCATION _____

PROJECT _____

DATE _____



-22 Oiled Bronze



-16 Gray

LIGHT SOURCE 1 x 10.1W LED, 3000K, CRI 90

LUMINAIRE POWER 13.0W at 120V

RATED LIFE 60000 hr RL

OPTIONAL COLOR TEMPERATURES 2700K, 3500K, 4000K

LUMEN OUTPUT Delivered: 531 lm (LM-79)

INPUT VOLTAGE 120V or 277V

DRIVER OUTPUT 350 mA, 12W

DIMMING 0-10v & Phase (ELV) Dimming - 50/60Hz 100% to 10% Dimming



CONSTRUCTION Cast Aluminium and Polycarbonate

DIFFUSER - Polished White Polycarbonate

FINISHES Gray (-16), Oiled Bronze (-22)

MOUNTING 4" Octagonal J-Box, 2"x3" J-Box*
* Must be mounted horizontally
(Installer must provide a bead of caulk between fixture housing and mounting surface)

STANDARDS ETL Wet, ADA compliant, Conforms to UL STD 1598, Certified CAN/CSA, STD C22.2 No 250.0.



DIMENSIONS

W: 4.25"

H: 16.50"

Ext: 2.25"

M.C: 8.00" From top of fixture

Order example for standard fixture:

3-730-22 (x- Voltage - xxx-Sequence # - xx-Finish)

3: 120v, 37: 277v

Order example for optional color temperatures: **3-730-2722**

27: 2700K, 35: 3500K, 40: 4000K

