

Facet

This versatile modern thin-trim 2-, 4- and 6-inch gimbal with multi-directional adjustable swivel produces a bright glow with minimal glare as a result of its regressed light source. Ideal for general lighting or for areas requiring a directional light to showcase unique elements or to create dramatic wall-wash effects.

UPGRADE

WET LOW-GLARE SWIVEL/DIRECTIONAL 30° ETL US Intertek IC RATED

AIR TIGHT 2700k 3000k 3500k 4000k 5000k COLOR TEMPERATURE



Model	Size	Watts	Delivered lumens	LED lumens	CRI	Color °T	Voltage
RGM2-CC	2"	8 W	660 lm	800 lm	90	2700, 3000, 3500, 4000, 5000 K	120 V
RGM4-CC	4"	12 W	1200 lm	1400 lm	90		120 V
RGM6-CC	6"	20 W	1500 lm	1800 lm	90		120 V

Specifications

Every fixture includes a junction box with integrated dimmable driver
 Can be daisy chained
 Superior LED performance and lifespan
 Regressed light source
 Minimal heat emission
 Aluminum construction
 Switch-selectable CCT: 2700K/3000 K/3500 K/4000 K/5000 K
 IC certification (suitable for direct contact with insulation)
 Air-tight certified as per ASTM E283-04
 40° beam angle
 30° tilting, 360° rotation
 Suitable for wet locations
 Refer to website for dimmer compatibility
 Ideal operating temperature:
 -20° to 40° C
 5-year warranty

Finish

- **BK** Black
- **WH** White

Accessories

- RFP-UNI**
Universal rough-in plate
- RFP-23**
Rough-in plate for 2" model
- RFP-46**
Rough-in plate for 4" and 6" models

Order example

RGM4-CC-BK
 4" gimbal recessed downlight with 1050 Lumens at 3000 K in a black finish

Note

Other Color °T and Finishes available, but may require MOQ's and longer lead times. Please contact your DALI representative for more information.

