SATCO' NUVO

Project Name

Location

Prepared By



NUVO TH495

12W LED PISTON TRACK HEAD

Notes

[www] 12-27-2021 01:40:40

General	
Status	Active
Туре	Track Head
Wattage	12W
Finish	Black
Beam Angle	36
CCT (Kelvin)	3000K
Temperature	Warm White
Base	Integrated LED
ANSI Base	Integrated LED
Indoor or Outdoor Fixture	Indoor
Specifications	
CRI	90
Lumen Output	1020L
Rated Hours	30000
Voltage	120V
Dimmable	Yes-Dimmable
Compatible Dimmers	Forward Phase or Reverse Phase or Phase Selectable
Weight (lb.)	0.77
Dimensions	
Height (in.)	2.75
Width (in.)	2.75
	2.75 2.75
Width (in.)	
Width (in.) Length (in.)	2.75
Width (in.) Length (in.) Extension (in.)	2.75
Width (in.) Length (in.) Extension (in.) Compliance	2.75 5.75
Width (in.) Length (in.) Extension (in.) Compliance Safety Listing	2.75 5.75 cETLus
Width (in.) Length (in.) Extension (in.) Compliance Safety Listing Location Rating	2.75 5.75 cETLus Dry
Width (in.) Length (in.) Extension (in.) Compliance Safety Listing Location Rating UL Application	2.75 5.75 cETLus Dry Ceiling
Width (in.) Length (in.) Extension (in.) Compliance Safety Listing Location Rating UL Application Energy Star	2.75 5.75 CETLus Dry Ceiling No
Width (in.) Length (in.) Extension (in.) Compliance Safety Listing Location Rating UL Application Energy Star California Status	2.75 5.75 CETLus Dry Ceiling No California T24 Compliant
Width (in.) Length (in.) Extension (in.) Compliance Safety Listing Location Rating UL Application Energy Star California Status California Prop 65	2.75 5.75 Dry Ceiling No California T24 Compliant Lead
Width (in.)Length (in.)Extension (in.)ComplianceSafety ListingLocation RatingUL ApplicationEnergy StarCalifornia StatusCalifornia Prop 65RoHS Compliant	2.75 5.75 Dry Ceiling No California T24 Compliant Lead Yes
Width (in.)Length (in.)Extension (in.)ComplianceSafety ListingLocation RatingUL ApplicationEnergy StarCalifornia StatusCalifornia Prop 65RoHS CompliantFCC Compliant	2.75 5.75 Dry Ceiling No California T24 Compliant Lead Yes

For More Information Visit: <u>http://www.satco.com/</u>

