

Fixture Type: Catalog Number: Project:

Reflex

17W H/J/L Track Luminaire

System Type	Model	Beam	Color Temp & CRI	Lumens	CBCP	Finish
H J L	LED17	F 45° S 20°	27 2700K - 85 30 3000K - 85 35 3500K - 85 40 4000K - 85 27 2700K - 85 30 3000K - 85 35 3500K - 85 40 4000K - 85	910 860 950 1035 990 990 1025 1125	1225 1145 1280 1375 3440 3590 3420 3780	BK Black BN Brushed Nickel WT White

Example: H-LED17F-27-BK

DESCRIPTION

High-performance and precise thermal management with robust die-cast construction makes this luminaire perfect for general, accent and wall wash applications in residential and commercial environments.

FEATURES

- · Accepts 1 lens/accessory
- 360° horizontal rotation and 180° vertical aiming
- Free of projected heat, UV and IR radiation
- · Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

Die-cast aluminum Construction:

17W Power:

120 VAC, 50/60Hz Input: ELV: 100-10% Dimming: Integrated LED Light Source:

3 Step Mac Adam Ellipse

Clear Lens Lens: 100000 Hours Rated Life:

Electrostatically Powder Coated:Black, Electrostatically Finish:

Powder Coated::White, Electrostatically Powder

Coated:::Brushed Nickel

-4°F to 104°F (-20°C to 40°C) **Operating Temp:** ETL, cETL, Dry Location Listed Standards:




Location:

FINISHES:



Nickel

LINE DRAWING:





Reflex 17W H/J/L Track Luminaire

Fixture Type:	
Catalog Number:	
Project:	
Location:	

ACCESSORIES			
	Model	Description	Finish
	LENS-20-RED LENS-20-GRN LENS-20-BLU LENS-20-AMB	Colored Lens Colored Lens Colored Lens Colored Lens	Red Green Blue Amber
	LENS-20-FR	Clear/Frosted Lens	Frosted
	LENS-20-SPR	Spread Lens	Spread Lens
	LENS-20-BEL	Beam Elongating Lens	Beam Elongating