


# 120 V Powerled linear

Long runs and flexibility are the primary features of our smooth PowerLED linears. A sleek, driverless connection ensures smooth and continuous light in every application.



Model	Size	Watts	Delivered lumens	LED lumens	CRI	Color °T	Voltage
<b>6009CC</b>	9"	3 W	250 lm	300 lm	80	2700 K/ 3000 K/ 3500 K/ 4000 K/ 5000 K	120 V
<b>6012CC</b>	12"	4 W	330 lm	400 lm	80	2700 K/ 3000 K/ 3500 K/ 4000 K/ 5000 K	120 V
<b>6024CC</b>	24"	8 W	675 lm	800 lm	80	2700 K/ 3000 K/ 3500 K/ 4000 K/ 5000 K	120 V
<b>6036CC</b>	36"	12 W	1080 lm	1200 lm	80	2700 K/ 3000 K/ 3500 K/ 4000 K/ 5000 K	120 V
<b>6048CC</b>	48"	16 W	1300 lm	1800 lm	80	2700 K/ 3000 K/ 3500 K/ 4000 K/ 5000 K	120 V

### Specifications

Switch-selectable CCT  
 Over 50,000 hours of service life  
 Dimmable with regular low-voltage electronic dimmers  
 Smooth linear wide spread  
 Minimal heat emission  
 Robust construction  
 Multiple fixtures can be linked together (up to 200W)  
 Refer to website for dimmer compatibility  
 5-year warranty

### Note

Junction box model 6000-JB or power cord model 6000-ACCPC are required for installation. Sold separately.

Other Color °T and Finishes available, but may require MOQ's and longer lead times. Please contact your DALs representative for more information.

### Accessories

**6000-ACCE06**  
6" extension cord  
**6000-ACCE24**  
24" extension cord  
**6000-ACCE60**  
60" extension cord  
**6000-ACCLR**  
Kit of left and right L connectors  
**6000-ACCPC**  
6' power cord  
**6000-JB**  
Junction box


### Finish

● **SBA** Sandblasted aluminum


### Order example

**6012CC-SBA**  
12" LED cove strip with a 4W LED array with 330 lumens at 3000K in a sandblasted aluminum finish


**6009CC**




**6012CC**



**6024CC**



**6036CC**



**6048CC**

