

New Item



15072 CO

ACRYLIC LENS STEP LIGHT/ LOUVERED STEP LIGHT

Designed to be integrated into outdoor steps. Casts a low, even spread of light. Available with louvered or white acrylic faceplate.


SPECIFICATIONS

Housing Stamped copper, brass or aluminum faceplate with white reflectors and zinc plated steel housing. For outdoor use only. For recessed installations.

Finish Copper, Brass, Textured Architectural Bronze, Textured White (15072 only)

Wiring Wire connections must be made inside junction box. 12-Volt wedge base socket.

Light Bulb 11.6-W. Max. 912X (15593CLR) (nominal at 12-Volts) supplied. Can also take 6.5-W. 918X (15592CLR) and 4-W. 901X (15540CLR). Copper, Bronzed Brass and Brass can only take 6.5-W. 918X (15592CLR). 90° supply wire required. ♦



15070
White acrylic lens

15070 – Footcandles/Distance from Fixture Center

Mounting Height	.5'	1'	1.5'	2'	2.5'	3'	3.5'	4'
6"	2.1	.5	.1	-	-	-	-	-
12"	1.2	.98	.5	.2	.1	.02	-	-



15072
Louver face

15072 – Footcandles/Distance from Fixture Center

Mounting Height	.5'	1'	1.5'	2'	2.5'	3'	3.5'	4'
6"	2.6	.3	.09	-	-	-	-	-
12"	1.6	1.2	.54	.08	.1	.04	-	-

New Item



15072 BR



15072 AZT/WHT

New Item



15070 BR

New Item



15070 CO



15070 AZT

15070

Housing Stamped copper (CO), brass (BR) or aluminum (AZT) faceplate with white reflectors and zinc plated steel housing. For outdoor use only. For recessed installations. White acrylic diffuser.

Finish Copper, Brass, Textured Architectural Bronze

Wiring Wire connections must be made inside junction box. 12-Volt wedge base socket.

Light Bulb 11.6-W. Max. 912X (15593CLR) light bulb (nominal at 12-Volts) supplied. Can also use 15592CLR and 15540CLR. 90° supply wire required.