

WAC LIGHTING

VENTRIX

Stealth Wall Wash

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Model & size	Power	Watt	Beam	Color Temp & CRI	Delivered Lumens	Finish	
S2WW12 12"	1	7W	A Asym	927 2700K - 90	450	BK Black	
	1	7W	A Asym	930 3000K - 90	470		
	1	7W	A Asym	935 3500K - 90	490		
	1	7W	A Asym	940 4000K - 90	500		
	2	10.5W	A Asym	927 2700K - 90	620		
	2	10.5W	A Asym	930 3000K - 90	650		
	2	10.5W	A Asym	935 3500K - 90	680		
	2	10.5W	A Asym	940 4000K - 90	690		
	3	14.5W	A Asym	927 2700K - 90	830		
	3	14.5W	A Asym	930 3000K - 90	870		
	3	14.5W	A Asym	935 3500K - 90	920		
	3	14.5W	A Asym	940 4000K - 90	930		
	S2WW24 24"	1	12W	A Asym	927 2700K - 90		810
		1	12W	A Asym	930 3000K - 90		850
1		12W	A Asym	935 3500K - 90	890		
1		12W	A Asym	940 4000K - 90	910		
2		19.5W	A Asym	927 2700K - 90	1200		
2		19.5W	A Asym	930 3000K - 90	1260		
2		19.5W	A Asym	935 3500K - 90	1330		
2		19.5W	A Asym	940 4000K - 90	1350		
3		27.5W	A Asym	927 2700K - 90	1610		
3		27.5W	A Asym	930 3000K - 90	1690		
3		27.5W	A Asym	935 3500K - 90	1780		
3		27.5W	A Asym	940 4000K - 90	1810		
S2WW48 48"		1	24W	A Asym	927 2700K - 90	1620	
		1	24W	A Asym	930 3000K - 90	1700	
	1	24W	A Asym	935 3500K - 90	1790		
	1	24W	A Asym	940 4000K - 90	1820		
	2	35W	A Asym	927 2700K - 90	2400		
	2	35W	A Asym	930 3000K - 90	2530		
	2	35W	A Asym	935 3500K - 90	2650		
	2	35W	A Asym	940 4000K - 90	2700		
	3	53W	A Asym	927 2700K - 90	3220		
	3	53W	A Asym	930 3000K - 90	3390		
	3	53W	A Asym	935 3500K - 90	3560		
	3	53W	A Asym	940 4000K - 90	3630		

Example: **S2WW12-1-A927BK**

DESCRIPTION

The only lighting, power, and control system complete with lighting elements designed for discriminating performance. Configure VENTRIX for your retail, restaurant, commercial office, or residential lighting plan.

FEATURES

- Provide even illumination on walls or ceilings without glare
- To enable access to VENTRIX element releasing tabs, maintain at least 3" of free channel space
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

Construction:	Extruded aluminum body, diecast aluminum endcaps with polycarbonate lens
Power:	7W, 10.5W, 12W, 14.5W, 19.5W, 24W, 27.5W, 35W, 53W
Input:	48 VDC
Dimming:	ELV: 100-0.1% , 0-10V: 100-0.1%, TRIAC: 100-0.1%
Light Source:	Integrated LED 3 Step Mac Adam Ellipse
Lens:	Clear Lens
Rated Life:	50000 Hours
Mounting:	Installs magnetically and mechanically into VENTRIX system, Can be mounted on ceiling or wall vertically or horizontally
Finish:	Electrostatically Powder Coated: Black



FINISHES:



Black


LINE DRAWING:

Operating Temperature: 40°F to 104°F (5°C to 40°C) | Phone: (800) 526-2585 | Fax: (800) 526-2585 | Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050


WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. May 2024

WAC LIGHTING

Standards: UL, cUL, Dry Location Listed, Title 24 JA8 Compliant



S2WW12



S2WW24, 48